



### Main

Product Range	Type S
Component type	Selector switch
Used with	Contactors and starters

### Complementary

NEMA size	0 4 00 5 1 3 2 6 7
Marking	HAND-OFF-AUTO
Mounting mode	Panel-mounted
Rated breaking capacity	6 A 120 V AC inductive control circuit UL 508 3 A 240 V AC inductive control circuit UL 508 1.2 A 600 V AC inductive control circuit UL 508 10 A 600 V AC resistive control circuit UL 508 1.1 A 125 V DC resistive control circuit UL 508 0.55 A 250 V DC resistive control circuit UL 508 0.2 A 600 V DC resistive control circuit UL 508
Height	1.88 in (47.75 mm)
Width	3.81 in (96.77 mm)
Maximum Depth	5.63 in (143.00 mm)
Net Weight	0.82 lb(US) (0.37 kg)

### Environment

NEMA degree of protection	NEMA 1
Product certifications	UL Recognized CSA


### Ordering and shipping details

Category	21761 - 9999 DISCOUNT CP1
Discount Schedule	CP1
GTIN	00785901030164
Nbr. of units in pkg.	1
Package weight(Lbs)	0.82 lb(US) (0.37 kg)
Returnability	Yes
Country of origin	MX

## Packing Units

Package 1 Height	3.30 in (8.382 cm)
Package 1 width	4.50 in (11.430 cm)
Package 1 Length	6.40 in (16.256 cm)

## Offer Sustainability

California proposition 65	WARNING: Cancer and Reproductive Harm - <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
EU RoHS Directive	Under investigation
China RoHS Regulation	 <a href="#">China RoHS Declaration</a>

## Contractual warranty

Warranty	18 months
----------	-----------