



### Main

Product Range	Type S
Component type	Push-button
Used with	Contactors starter

### Complementary

NEMA size	1 00 2 0 3
Marking	START-STOP
Mounting mode	Panel-mounted
Rated breaking capacity	3 A 120 V AC inductive control circuit UL 508 1.5 A 240 V AC inductive control circuit UL 508 0.6 A 600 V AC inductive control circuit UL 508 5 A 600 V AC resistive control circuit UL 508
Height	1.02 in (25.8 mm)
Width	2.58 in (65.5 mm)
Maximum Depth	24.00 in (609.6 mm)
Net Weight	0.37 lb(US) (0.17 kg)

### Environment

NEMA degree of protection	NEMA 1
Product certifications	CSA UL Listed UL Recognized

### Ordering and shipping details

Category	21761 - 9999 DISCOUNT CP1
Discount Schedule	CP1
GTIN	00785901867234
Nbr. of units in pkg.	1
Package weight(Lbs)	0.37 lb(US) (0.17 kg)
Returnability	Yes
Country of origin	MX

### Packing Units

Package 1 Height	1.90 in (4.826 cm)
Package 1 width	3.90 in (9.906 cm)
Package 1 Length	5.70 in (14.478 cm)

## Offer Sustainability

California proposition 65	WARNING: Cancer and Reproductive Harm - <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
EU RoHS Directive	Under investigation
China RoHS Regulation	 <a href="#">China RoHS Declaration</a>

## Contractual warranty

Warranty	18 months
----------	-----------