

Main

Product Range	Type S
Component type	Push-button
Used with	Contactors starter

Complementary

NEMA size	2 0 6 4 5 3 7 00 1
Marking	START-STOP ON-OFF
Mounting mode	Panel-mounted
Rated breaking capacity	6 A 120 V AC inductive control circuit UL 508 3 A 240 V AC inductive control circuit UL 508 1.2 A 600 V AC inductive control circuit UL 508 10 A 600 V AC resistive control circuit UL 508 1.1 A 125 V DC resistive control circuit UL 508 0.55 A 250 V DC resistive control circuit UL 508 0.2 A 600 V DC resistive control circuit UL 508

Environment

NEMA degree of protection	NEMA 1 NEMA 12/3R
Product certifications	UL Recognized CSA


Ordering and shipping details

Category	21761 - 9999 DISCOUNT CP1
Discount Schedule	CP1
GTIN	00785901030171
Nbr. of units in pkg.	1
Package weight(Lbs)	1.08 lb(US) (0.49 kg)
Returnability	Yes
Country of origin	MX

Packing Units

Package 1 Height	3.40 in (8.636 cm)
Package 1 width	4.40 in (11.176 cm)
Package 1 Length	6.30 in (16.002 cm)

Offer Sustainability

California proposition 65	WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov
EU RoHS Directive	Under investigation
China RoHS Regulation	 China RoHS Declaration

Contractual warranty

Warranty	18 months
----------	-----------