



### Main

Product	Wall flange
Range	I-Line

### Complementary

Rated Operational Voltage	600 V AC/DC 50/60 Hz
Length	13.32 in (338.33 mm)
Width	10.26 in (260.60 mm)
For Use with	Busbar trunking 1600 A aluminium

### Environment

Standards	UL 857 CSA C22.2 No 27:1994 IEC 61439-6
-----------	---

### Ordering and shipping details

Category	20199-WALL FLANGES/END CLOSURES
Discount Schedule	PE8
GTIN	00785901812593
Package weight(Lbs)	4.78 lb(US) (2.168 kg)
Returnability	Yes
Country of origin	US

### Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Bisphenol A (BPA), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
RECh Regulation	<a href="#">RECh Declaration</a>
RECh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>

---

Environmental Disclosure	<a href="#">Product Environmental Profile</a>
PVC free	Yes

---

### Contractual warranty

---

Warranty	18 months
----------	-----------

---