



### Main

Product	Double Throw Safety Switch
Current Rating	30 A
Certifications	UL Listed
Enclosure Rating	NEMA 1 steel
Factory Installed Neutral	None
Disconnect Type	Non-fusible disconnect
Mounting Type	Surface
Number of Poles	4
Voltage Rating	240 V AC
Wire Size	AWG 12...AWG 2 aluminium AWG 14...AWG 2 copper

### Complementary

Width	11.75 in (298.45 mm)
Height	10 in (254.00 mm)
Maximum Depth	4.75 in (120.65 mm)
Tightening torque	35 Lbf.In (3.95 N.m) 0.00...0.01 in <sup>2</sup> (2.08...5.26 mm <sup>2</sup> ) AWG 14...AWG 10) 40 Lbf.In (4.52 N.m) 0.01 in <sup>2</sup> (8.37 mm <sup>2</sup> ) AWG 8) 45 Lbf.In (5.08 N.m) 0.02...0.03 in <sup>2</sup> (13.3...21.15 mm <sup>2</sup> ) AWG 6...AWG 4) 50 lbf.in (5.65 N.m) 0.04...0.05 in <sup>2</sup> (26.67...33.62 mm <sup>2</sup> ) AWG 3...AWG 2)



### Ordering and shipping details

Category	00033 - DT SWITCH,NEMA1
Discount Schedule	DE1
GTIN	00785901454762
Nbr. of units in pkg.	1
Package weight(Lbs)	20.62 lb(US) (9.35 kg)
Returnability	No
Country of origin	MX

### Packing Units

Package 1 Height	3.94 in (10.000 cm)
Package 1 width	3.84 in (9.751 cm)
Package 1 Length	1.87 in (4.750 cm)

### Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
RECh Regulation	 RECh Declaration
RECh free of SVHC	Yes
EU RoHS Directive	Compliant  EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes

RoHS exemption information	 <a href="#">Yes</a>
China RoHS Regulation	 <a href="#">China RoHS Declaration</a>
Environmental Disclosure	 <a href="#">Product Environmental Profile</a>

Contractual warranty

Warranty	18 months
----------	-----------