

HOM240

Mini circuit breaker, Homeline, 40A, 2 pole, 120/240 VAC, 10 kA AIR, standard type, plug in mount



Main

Product	Miniature circuit-breaker
Range	Homeline
Current Rating	40 A
Certifications	UL Listed
Voltage Rating	120/240 V AC
Mounting Type	Plug-in
Number of Poles	2P
Short Circuit Current Rating	10 kA
Number of Spaces	2
Circuit Breaker Type	Standard
Ratings	HACR rated
Electrical Connection	Box lugs
Wire Size	AWG 8...AWG 2 aluminium/copper)1

Complementary

Height	3.13 in (79.50 mm)
Width	2 in (50.80 mm)
Maximum Depth	2.98 in (75.69 mm)
Tightening torque	40.71 lbf.in (4.6 N.m) AWG 8...AWG 2)

Environment

Ambient air temperature for operation	104 °F (40 °C)
---------------------------------------	----------------

Ordering and shipping details

Category	00046 - HOM/T 15-30A 1P; 15-60A 2P
Discount Schedule	DE3D
GTIN	00785901065302
Nbr. of units in pkg.	5
Package weight(Lbs)	0.7 lb(US) (0.32 kg)
Returnability	Yes
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	2.00 in (5.08 cm)
Package 1 width	3.00 in (7.62 cm)
Package 1 Length	3.20 in (8.128 cm)
Unit Type of Package 2	BB1
Number of Units in Package 2	5
Package 2 Weight	3.58 lb(US) (1.624 kg)
Package 2 Height	3.20 in (8.128 cm)
Package 2 width	2.60 in (6.604 cm)
Package 2 Length	10.20 in (25.908 cm)

Unit Type of Package 3	CAR
Number of Units in Package 3	50
Package 3 Weight	36.65 lb(US) (16.624 kg)
Package 3 Height	10.40 in (26.416 cm)
Package 3 width	6.90 in (17.526 cm)
Package 3 Length	16.60 in (42.164 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	Lifetime
----------	----------