L211N

Safety switch, light duty, fusible, 30A, 2 poles, 120 VAC, NEMA 1, neutral factory installed





Main

Product	Single Throw Safety Switch
Current Rating	30 A
Enclosure Rating	NEMA 1
Factory Installed Neutral	Neutral (factory installed)
Disconnect Type	Fusible disconnect
Fuse Type	Plug
Mounting Type	Surface
Number of Poles	2
Duty Rating	Light duty
Voltage Rating	240 V AC
Wire Size	AWG 14AWG 8 copper AWG 12AWG 8 aluminium

Complementary

Width	6.13 in (155.70 mm)
Maximum Horse Power Rating	0.5 Hp 120 V AC 5060 Hz 1 phase NEC 240.6 2 Hp 120 V AC 5060 Hz 1 phase NEC 430.52 1.5 Hp 240 V AC 5060 Hz 1 phase NEC 240.6 3 hp 240 V AC 5060 Hz 1 phase NEC 240.6
Height	7.63 in (193.80 mm)
Maximum Depth	4 in (101.60 mm)
Tightening torque	30 Lbf.In (3.39 N.m) 0.000.01 in² (2.0828.367 mm²) AWG 14AWG 8) 30 lbf.in (3.39 N.m) 0.010.01 in² (3.3078.367 mm²) AWG 12AWG 8)

Ordering and shipping details

0 11 0	
Category	00057 - LIGHT DUTY SW, NEMA1, 30A
Discount Schedule	DE1A
GTIN	00785901090526
Nbr. of units in pkg.	1
Package weight(Lbs)	3.33 lb(US) (1.51 kg)
Returnability	Yes
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE	
Package 1 Height	5.50 in (13.97 cm)	
Package 1 width	6.50 in (16.51 cm)	
Package 1 Length	8.30 in (21.082 cm)	
Unit Type of Package 2	PAL	
Number of Units in Package 2	200	
Package 2 Weight	682.20 lb(US) (309.44 kg)	
Package 2 Height	40.00 in (101.6 cm)	
Package 2 width	40.00 in (101.6 cm)	
Package 2 Length	48.00 in (121.92 cm)	

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	☑ REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EEU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	₫Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	18 months

Approximate Dimensions

