HOM2175SB

Surge protection device, Surgebreaker, 22.5kA, 120/240 VAC, 1 phase, 3 wire, SPD type 2



Main

Product	Surge protection device
Range	Surge Breaker Homeline

Complementary

Complementary		
Surge Current	22.5 kA	
Voltage Rating	120/240 V AC	
Number of Phases	1 phase	
Wiring Configuration	3-wire	
MCOV	150 V 300 V	
Rated Current	5 kA	
SCCR	22 kA	
Local Signalling	1 LED green normal operation	
Product destination	Load center Homeline	
Height	3.7 in (93.98 mm)	
Width	2 in (50.80 mm)	
Depth	2.6 in (66.04 mm)	

Environment

Enclosure Rating	NEMA 1
Standards	UL 1449:ed. 4: type II
Ambient Operating	149 °F (65 °C)

Ordering and shipping details

Category	08461 - SURGE PROTECTION RESI
Discount Schedule	DE1B
GTIN	00785901210900
Nbr. of units in pkg.	1
Package weight(Lbs)	0.81 lb(US) (0.37 kg)
Returnability	Yes
Country of origin	MX
Country of origin	MX

Packing Units

Package 1 Height	2.20 in (5.588 cm)
Package 1 width	2.70 in (6.858 cm)
Package 1 Length	5.30 in (13.462 cm)

Offer Sustainability

Warranty

EU RoHS Directive	Under investigation	
Contractual warranty		

18 months