



Main

Product or component type	Circuit breaker
Range of product	PowerPact H
Trip Unit Type	Thermal-magnetic
Breaking capacity code	G

Complementary

Line Rated Current	110 A
Number of Poles	2P
Interrupt Rating	20 KA at 500 V DC 65 KA 240 V AC 35 KA 480 V AC 18 KA 600 V AC 20 kA 250 V DC
[Ue] rated operational voltage	250 V DC 600 V AC 500 V DC
Continuous current rating	80 %
Mounting mode	I-Line
Electrical connection	I-Line connection line Lugs load
Magnetic hold current	900 A
Magnetic tripping current	1700 A
Wire Gauge	AWG 14...AWG 3/0 aluminium/copper
Tightening torque	44.25 lbf.in (5 N.m) 0.00...0.15 in ² (2.5...95 mm ²) AWG 14...AWG 3/0)
Phase	CB
Height	9.73 in (247.14 mm)
Width	2.94 in (74.68 mm)
Maximum Depth	4.8 in (121.92 mm)

Environment

Product certifications	CE IEC UL Listed CSA
Ambient air temperature for operation	104 °F (40 °C)

Ordering and shipping details

Category	01117-HG, HJ, JG, JJ I-LINE BREAKER/SWITC
Discount Schedule	DE2
Package weight(Lbs)	3.00 lb(US) (1.361 kg)
Returnability	Yes
Country of origin	US

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: DINP, which is known to the State of California to cause cancer, and DIDP, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
PVC free	Yes

Contractual warranty

Warranty	18 months
----------	-----------