



### Main

Product or Component Type	Circuit breaker
Range	I-Line
Trip Unit Technology	Thermal-magnetic
Circuit Breaker Rating Code	H

### Complementary

Rated Current	300 A
Number of Poles	3P
Breaking Capacity Interrupt Rating	65 KA 240 V AC 35 KA 480Y/277 V AC 35 KA 480 V AC 25 KA 600Y/347 V AC 25 KA 600 V AC 50 KA 250 V DC 20 kA at 500 V DC
Rated Operational Voltage	600 V AC 250 V DC 500 V DC
Mounting Mode	I-Line
Electrical Connection	Lugs load I-Line connection line
Magnetic Hold Current	1500 A
Magnetic Tripping Current	3000 A
Terminal Type	AL400LA
AWG Wire Gauge	AWG 1...600 kcmil aluminium/copper)1 AWG 1...250 kcmil aluminium/copper)2
Height	12.5 in (317.50 mm)
Width	6 in (152.40 mm)
Depth	4 in (101.60 mm)

### Environment

Certifications	UL Listed CSA
----------------	------------------

### Ordering and shipping details

Category	01040 - LA/LH BRKR, SW, MAG-GARD
Discount Schedule	DE2
GTIN	00785901339410
Nbr. of units in pkg.	1
Package weight(Lbs)	18.28 lb(US) (8.29 kg)
Returnability	Yes
Country of origin	MX

## Packing Units

Package 1 Height	9.20 in (23.368 cm)
Package 1 width	11.70 in (29.718 cm)
Package 1 Length	17.60 in (44.704 cm)

## Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: DINP, which is known to the State of California to cause cancer, and DIDP, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
PVC free	Yes
Halogen content performance	Halogen free plastic parts product

## Contractual warranty

Warranty	18 months
----------	-----------