



Main

Range	Masterpact
Product or component type	Ethernet interface module
Condition of use	With specific accessories
Device application	Communication
Range compatibility	Masterpact MTZ2 circuit breaker Masterpact MTZ3 circuit breaker
Device mounting	Embedded

Complementary

Communication gateway	Ethernet TCP/IP to Modbus
Communication network type	ULP, CANopen USB Ethernet, Ethernet TCP/IP 10/100 Mbps RJ45
Mounting mode	Drawout
Mounting support	DIN rail
Localisation on device	Chassis
Maximum supply current	3 A
Power consumption in W	72 W
Product certifications	CE FCC EAC
Standards	IEC 60947-6-2 IEC 60950 IACS E10
Height	2.01 in (51 mm)
Width	2.01 in (51 mm)
Maximum Depth	2.07 in (52.5 mm)
Net Weight	0.17 lb(US) (0.075 kg)
Web server	Embedded
Provided equipment	1 instruction sheet
Offer type	Spare part

Environment

IP degree of protection	IP30
Ambient air temperature for operation	-4...158 °F (-20...70 °C)

Ordering and shipping details

Category	01257 - MASTERPACT MTZ ACCESS
Discount Schedule	DE2F
Nbr. of units in pkg.	1
Package weight(Lbs)	1 lb(US) (0.45 kg)
Returnability	No

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	1.91 in (4.85 cm)
Package 1 width	2.01 in (5.1 cm)
Package 1 Length	2.07 in (5.25 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: DINP, which is known to the State of California to cause cancer, and DIDP, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
Halogen content performance	Halogen free plastic parts product