



## Main

Range of product	PowerPact L
Product or component type	Circuit breaker
Trip Unit Type	Electronic, standard, Micrologic 3.3, LI
Interrupt Code	L

## Complementary

Line Rated Current	250 A
Number of Poles	3P
Interrupt Rating	125 KA 240 V AC 100 KA 480 V AC 50 kA 600 V AC
Voltage Rating	600 V AC
Continuous current rating	80 %
Protection technology	Current limiter
Mounting mode	Unit mount
Electrical connection	Lugs load Lugs line
Terminal Type	AL400L61K3
Wire Size	AWG 2...500 kcmil aluminium)1 AWG 2...600 kcmil copper)1
Tightening torque	442.54 Lbf.in (50 N.m) 0.05...0.37 in <sup>2</sup> (35...240 mm <sup>2</sup> ) AWG 2...500 kcmil) 442.54 lbf.in (50 N.m) 0.05...0.47 in <sup>2</sup> (35...300 mm <sup>2</sup> ) AWG 2...600 kcmil)
Height	11.3 in (287.02 mm)
Width	5.5 in (139.70 mm)
Maximum Depth	6.61 in (167.89 mm)

## Environment

Product certifications	CSA 22-2 CCC IEC CE UL 489 NMX NEMA
------------------------	---

## Ordering and shipping details

Category	01116-L ELEC TRIP UNIT MOUNT BREAKER/SW
Discount Schedule	DE2
GTIN	00785901489481
Package weight(Lbs)	15.00 lb(US) (6.804 kg)
Returnability	Yes
Country of origin	US

## Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: DINP, which is known to the State of California to cause cancer, and DIDP, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End Of Life Information</a>
PVC free	Yes

## Contractual warranty

Warranty	18 months
----------	-----------