



## Main

Product or Component Type	Motor Circuit Protector
Trip Unit Technology	Thermal-magnetic

## Complementary

Rated Current	400 A
Number of Poles	3P
Breaking Capacity Interrupt Rating	42 KA 240 V AC 30 KA 480 V AC 22 KA 600 V AC 10 KA 125 V DC 10 kA 250 V DC
Rated Operational Voltage	600 V AC 250 V DC
Mounting Mode	Unit mount
Electrical Connection	Lugs load Lugs line
Magnetic Hold Current	2000 A
Magnetic Tripping Current	4000 A
Terminal Type	AL400LA
AWG Wire Gauge	AWG 1...600 kcmil aluminium/copper)1 AWG 1...250 kcmil aluminium/copper)2
Tightening Torque	115.06 Lbf.in (13 N.m) 0.07...0.47 in <sup>2</sup> (42...304 mm <sup>2</sup> ) AWG 1...600 kcmil 115.06 lbf.in (13 N.m) 0.07...0.20 in <sup>2</sup> (42...127 mm <sup>2</sup> ) AWG 1...250 kcmil
Height	11 in (279.40 mm)
Width	6 in (152.40 mm)
Depth	5.84 in (148.34 mm)

## Environment

Certifications	UL Listed CSA IEC
----------------	-------------------------

## Ordering and shipping details

Category	00935 - LAL/LHL BRKR, SW, MAG-GARD
Discount Schedule	DE2
GTIN	00785901650508
Nbr. of units in pkg.	1
Package weight(Lbs)	16.51 lb(US) (7.49 kg)
Returnability	Yes
Country of origin	MX

## Packing Units

Unit Type of Package 1	PCE
Package 1 Height	9.10 in (23.114 cm)
Package 1 width	11.50 in (29.21 cm)
Package 1 Length	17.50 in (44.45 cm)

## Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: DINP, which is known to the State of California to cause cancer, and DIDP, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
PVC free	Yes
Halogen content performance	Halogen free plastic parts product

## Contractual warranty

Warranty	18 months
----------	-----------