Product data sheet Characteristics

PBQ3660G 600A 600V Fusible Busway Plug-In Unit





Main

Product or component Section type

Complementary

Fixing mode Plug-in [Ue] rated operational voltage 600 V AC [le] rated operational current 600 A Number of poles 3 Busbar description Ground Fuse type H Disconnector device type Fusible disconnect			
[le] rated operational current 600 A Number of poles 3 Busbar description Ground Fuse type H	Fixing mode	Plug-in	
Number of poles 3 Busbar description Ground Fuse type H	[Ue] rated operational voltage	600 V AC	
Busbar description Ground Fuse type H	[le] rated operational current	600 A	
Fuse type H	Number of poles	3	
	Busbar description	Ground	
Disconnector device type Fusible disconnect	Fuse type	Н	
	Disconnector device type	Fusible disconnect	

Environment

Product certifications	UL
1 Toddot oci iliodilorio	
	CSA

Ordering and shipping details

Category	20203 - PBQ 600A FUSIBLE PLUGS
Discount Schedule	PE7
GTIN	00785901518365
Nbr. of units in pkg.	1
Package weight(Lbs)	190 lb(US) (86.18 kg)
Returnability	Yes
Country of origin	MX

Packing Units

Package 1 Height	2.02 ft (0.615 m)
Package 1 width	2.00 ft (0.610 m)
Package 1 Length	3.55 ft (1.082 m)

Offer Sustainability

Warranty

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Bisphenol A (BPA), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	[™] REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EPEU RoHS Declaration
Mercury free	Yes
RoHS exemption information	₫Yes
China RoHS Regulation	☑ China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	☑ End Of Life Information
PVC free	Yes

18 months