

McGill™ Incandescent Utility Lights

NEC/CEC:
Listed for Ordinary (Unclassified) Locations

Applications

- Ideal for food processing plants, barns, garages, warehouses, and workshops.
- Low cost, corrosion-resistant, enclosed utility lights, complete with base, wiring box, and globe, are convenient to use.

Features

- Fasten directly to walls, ceilings, or structural members — no separate outlet box required.
- Glass globe screws out for easy replacement of a A-21 bulb (not included) up to 150 Watts.
- High quality materials and sockets assure long, trouble-free service life.
- 88.9 mm (3.5 in) diameter; 241.3 mm (9.5 in) height
- Two 7.9 mm (0.31) diameter mounting holes on 111.3 mm (4.38 in) centers.
- Moisture-resistant construction with no exposed metal parts.
- Large compartment for easy wiring.
- Super strong, impact-resistant, thermoplastic mounting unit.
- For use up to 38 °C (100 °F) ambient temperature.
- Accommodates up to 150 Watts max. domestic A-21 bulbs.
- For use with either 12.7 mm (1.5) or 19.1 mm (0.75 in) rigid non-metallic conduit.

NEC/CEC Certification and Compliances

- UL Listed: E22558
- UL Standard: 1598
- CSA Certified: LL56247
- CSA Listed: C22.2 No. 250.0



606 with 1435-6

GENERAL UTILITY LIGHTS

 **Appleton**

McGill™ Incandescent Utility Lights

NEC/CEC:
Listed for Ordinary (Unclassified) Locations

	Wiring Compartment Cubic Decimeter (Cubic Inch)	Supply Wire Rating °C (°F)	Catalog Numbers	
			12.7 mm (0.5 in) Threaded Conduit Opening	19.1 mm (0.74) Threaded Conduit Opening
Utility light with glass globe				
For damp locations	0.25 (15)	125 (257)	600	601
For damp locations	0.25 (15)	105 (221)	C600 ①	C601 ①
For damp locations	0.20 (12)	60 (140)	603	604
For damp locations	0.20 (12)	60 (140)	C603 ①	C604 ①
Sealed unit for wet locations	0.20 (12)	60 (140)	605	606
Sealed unit for wet locations	0.20 (12)	60 (140)	C605 ①	C606 ①

Accessories and Replacement Parts — Additional plastic globes see Protect-O-Globes

	Catalog Number
Protective metal cage for glass globes only	1435-6
Base and socket only for 600, 640, and 650	610
Base and socket only for 601, 641, and 651	611
Base and socket only for 603, 643 and 653	5213-0623
Base and socket only for 604, 644 and 654	5213-0672
Base, socket, and seal assembly only for 605	5213-0637
Base, socket, and seal assembly only for 606	5213-0638
Socket only for 0.25 cubic decimeter (15 cubic inch) wiring compartment	600-3
Socket only for 0.20 cubic decimeter (12 cubic inch) wiring compartment	606-3
Glass globe only for 600, 601, 603, and 604 - 296.9 mm (6.69 in) long	0753
Glass globe only for 605 and 606 - 296.9 mm (6.69 in) long	0753-HR ②

GENERAL UTILITY LIGHTS

Appleton®

① Certified to meet the Canadian Electrical Code (CEC) only
② Heat resistant globes required for wet locations.