



Quality Products. Service Excellence.

## Type 4X Stainless Steel Splitter Box *CN4SBSS Series*

Hinge Door with Quarter Turn



### Application

- The splitter boxes are designed for distribution of up to 600 A (max) service using either 3 or 4 wires. 75° C conductor ampacity permitted.

### Standards

- CSA Type 3R, 12, 4X
- Complies with
  - IEC 60529, IP66

### Construction

- Formed 16 gauge Type 304 stainless steel (14 gauge on 30x24)
- Factory installed splitter blocks.
- Smooth, continuously welded seams ground smooth.
- Door stiffeners are provided where required for increased strength and rigidity - designed to also permit additional mounting options.
- Formed lip on enclosure to exclude flowing liquids and contaminants.
- Door latches feature the added safety of quarter turn slot requiring use of tool for opening
- Doors may be easily removed for modifications and are interchangeable.
- Seamless poured-in place gasket.
- Collar studs provided for mounting inner panel.
- Includes hardware kit with panel mounting nuts and sealing washers for wall mounting holes.
- Hinges are constructed from 304 stainless steel.
- Hinge pins are stainless steel.
- Inner panel is included.

### Finish

- Cover and enclosure are natural stainless steel with a smooth brushed finish.
- Inner panel is finished in white powder coating.

| 3 Wire      | 4 Wire      | CU/AL   | Enclosure |       |      | Optional      | Splitter        |
|-------------|-------------|---------|-----------|-------|------|---------------|-----------------|
| Part No.    | Part No.    | Amps    | H         | W     | D    | Grounding Kit | Block Reference |
| CN4SB73SS   | CN4SB74SS   | 70/70   | 12.00     | 10.00 | 5.00 | CGK125        | CSBL125B        |
| CN4SB103SS  | CN4SB104SS  | 125/120 | 15.00     | 10.00 | 5.00 | CGK125        | CSBL125B        |
| CN4SB203SS  | CN4SB204SS  | 225/180 | 18.00     | 12.00 | 5.00 | CGK225        | CSBL225         |
| CN4SB403SS  | CN4SB404SS  | 400/400 | 24.00     | 17.00 | 6.00 | CGK400        | CSBL400         |
| CN4SB603SS* | CN4SB604SS* | 600/600 | 30.00     | 24.00 | 7.00 | CGK600        | CSBL600         |

\* 14 gauge steel

Data subject to change without notice

