8539SCA13V06

NEMA Combination Starter, Type S, 25A HHL thermal magnetic circuit breaker, Size 1, 27A, 3 phase, 480 VAC coil, NEMA 12



Main

| Product | Combination Starter |
|----------------------|------------------------|
| Туре | S |
| Control Circuit Type | Common control circuit |

Complementary

| Complementary | | |
|-------------------------|---|--|
| Control Circuit Voltage | 440 V AC 50 Hz 480 V AC 60 Hz | |
| Starter Type | Non reversing | |
| Number of Poles | 3P | |
| Horsepower Rating | 7.5 Hp 460 V AC, 3 phase 10 hp 575 V AC, 3 phase | |
| Maximum Voltage Rating | 600 V AC | |
| Control Units | No control units | |
| Pilot Light | No indicator | |
| Auxiliary Contacts | Without | |
| Thermal overload type | Melting alloy 3 | |
| Disconnect Type | Thermal magnetic circuit breaker, 20 A | |
| | | |

Environment

| Enclosure Type | NEMA 12 painted sheet steel with external reset | |
|----------------|---|---|
| NEMA size | 1 | ٠ |

Ordering and shipping details

| Category | 21213 - 8538,39 SC,SD(NOT S*R,T,W) | |
|-----------------------|------------------------------------|--|
| Discount Schedule | CP1 | |
| GTIN | 00785901778943 | |
| Nbr. of units in pkg. | 1 | |
| Package weight(Lbs) | 45 lb(US) (20.41 kg) | |
| Returnability | Yes | |
| Country of origin | MX | |

Offer Sustainability

| EU RoHS Directive | Not compliant |
|-----------------------|------------------------|
| China RoHS Regulation | China RoHS Declaration |

Contractual warranty

| Warranty | 18 months | |
|----------|-----------|--|