8736SDG2V02S

NEMA Starter, Type S, reversing, horizontal, Size 2, 45A, 25 HP at 575 VAC, 5 kA SSCR, 3 phase, 3 pole, melting alloy overload, 120 VAC coil, NEMA 1



Main

Product Type	Starter	
Product Range	S	
Starter Type	Reversing	

Complementary

Complementary	
NEMA Size	2
Rated Current	45 A
Number of Poles	3P
Mounting Orientation	Horizontal
Wiring Mode	3 wires
Maximum Voltage Rating	600 V AC
Phase	3 phase
Type of Overload	Melting alloy 3
Horsepower Rating	10 HP 200 V AC 15 HP 230 V AC 25 HP 460 V AC 25 HP 575 V AC
SCCR	Circuit-breaker: 5 kA at 600 V AC Fuse: 5 kA at 600 V AC
Coil Voltage	110 V AC 50 Hz 120 V AC 60 Hz
Control Circuit Type	Separate control circuit
Control Units	No control units
Pilot Light	Without pilot light
Auxiliary Contacts	Without
Terminal Type	Screw clamp terminals
Height	14.13 in (358.90 mm)
Width	14.88 in (377.95 mm)
Depth	7.66 in (194.56 mm)

Environment

Enclosure Type	NEMA 1 painted sheet steel
Certifications	UL Listed CSA

Ordering and shipping details

Category	21272 - 8702,36 SC,SD(NOT S*R,T,W)	
Discount Schedule	CP1	
GTIN	00785901455646	
Nbr. of units in pkg.	1	
Package weight(Lbs)	30.85 lb(US) (13.993 kg)	
Returnability	No	
Country of origin	MX	

Packing Units

Unit Type of Package 1	PCE	
Package 1 Height	10.00 in (25.4 cm)	
Package 1 width	15.60 in (39.624 cm)	
Package 1 Length	16.60 in (42.164 cm)	

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
EU RoHS Directive	Not compliant
China RoHS Regulation	[™] China RoHS Declaration

Contractual warranty

Warranty	18 months
vvarianty	10 111011115
•	