8911DPSO23V09

Starter, Definite Purpose, nonreversing, 25A, 3 pole, 3 phase, 208 to 240VAC coil, melting alloy overload, open style



Main	
Product	Definite Purpose Starter
Ampere Rating	25 A
Horsepower Rating	2 Hp 115 V AC, 1 phase 5 Hp 230 V AC, 1 phase 10 Hp 230 V AC, 3 phase 15 Hp 460 V AC, 3 phase 20 hp 575 V AC, 3 phase
Maximum Voltage Rating	600 V AC
Control Circuit Voltage	220 V AC 50 Hz 208240 V AC 60 Hz
Phase	3 phase

Complementary

Enclosure Rating	Not rated (open device)	
Locked Rotor Amperes	150 A 230 V AC	
	125 A 460 V AC	
	100 A 575 V AC	
Number of Poles	3P	
Range	DPS	
Overload Type	Melting alloy	
Number of Thermal Units	3	

Ordering and shipping details

Category	21381 - 8911 DP	
Discount Schedule	CP1	
GTIN	00785901342793	
Nbr. of units in pkg.	1	
Package weight(Lbs)	2.29 lb(US) (1.039 kg)	
Returnability	Yes	
Country of origin	CN	

Packing Units

Unit Type of Package 1	PCE	
Package 1 Height	4.80 in (12.192 cm)	
Package 1 width	4.80 in (12.192 cm)	
Package 1 Length	8.00 in (20.32 cm)	

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals which are known to the State of California to cause Carcinogen and Reproductive harm.For more information go to www.p65warnings.ca.gov	
REACh Regulation	☐ REACh Declaration	
EU RoHS Directive	Compliant EEU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	€Yes	
China RoHS Regulation	☑ China RoHS Declaration	

Warranty 18 months