

1200VA Voltage Regulator - Automatic voltage regulation with surge protection

MODEL NUMBER: VR1208R



Description

1200 VA Automatic Voltage Regulation (AVR) system/Protects sensitive electronics, computer accessories and home theater equipment from power-related damage and performance problems/Extends the useful life of connected equipment by providing optimum voltage conditions for enhanced efficiency and cooler internal operating temperatures/Reliable transformer-based voltage correction circuits maintain 120V nominal output during voltage fluctuations between 100 and 145V/Two levels of voltage stabilization offer targeted response for overvoltages and brownouts/Prevents equipment damage and power related performance problems for computer accessories, printers, home theater equipment, a/v components and other sensitive electronic devices/AC surge and EMI/RFI noise suppression/Supports loads up to 1200 VA, 8 AC outlets/3-ft. (0.91 m) AC line cord/3 diagnostic LEDs display boost, cut and normal operation.

Features

- Maintains regulated 120V (+12%/-12%) nominal output over an input range of 100 to 145V
- Protects sensitive electronics, computer accessories and home theater equipment from power-related damage and performance problems
- Extends the useful life of connected equipment by providing optimum voltage conditions for enhanced efficiency and cooler internal operating temperatures
- Two levels of voltage stabilization offers response to overvoltages and brownouts
- Input voltages over 130V are reduced by 12% (+/- 3V)
- Input voltages below 110V are boosted by 12% (+/- 3V)
- 1200 VA output power
- EMI/RFI noise filtering prevents equipment interaction, system interference, lockups and other power-related audio and video artifacts
- 3 diagnostic LEDs indicate boost, cut and normal AVR operation

Highlights

- Automatic voltage regulation (AVR) and AC surge suppression
- Maintains regulated 120V nominal output over an input range of 100 to 145V
- 1200 VA
- 8 NEMA 5-15R outlets, 3-ft. (0.91 m) AC cord
- LEDs display boost, cut and normal operation

Package Includes

- VR1208R Line Conditioner
- Instruction manual with warranty information



- 8 protected NEMA5-15R outlets
- 3-ft. (0.91 m) AC power cord with NEMA5-15P input plug

Specifications

OVERVIEW	
UPC Code	037332144386
OUTPUT	
Output (VA)	1200
Nominal Output Voltage(s) Supported	120V
Output Receptacles	(8) 5-15R
Output Nominal Voltage	120V / 60Hz
Outlet Details	4 AVR / Surge NEMA 5-15R outlets; 4 Surge-only NEMA 5-15R outlets
PHYSICAL	
Shipping Dimensions (hwd / cm)	9.50 x 16.99 x 13.51
Shipping Dimensions (hwd / in.)	3.74 x 6.69 x 5.32
Shipping Weight (kg)	1.36
Shipping Weight (lbs.)	3.00
WARRANTY	
Product Warranty Period (Worldwide)	2-year limited warranty

© 2021 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice.

Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies:

<https://www.tripplite.com/products/product-certification-agencies>