SIEMENS

Data sheet US2:HF321NR



Siemens Low Voltage Circuit Protection Heavy Duty Safety Switch. 3-Pole 3-Fuse and solid neutral Fused in a type 3R enclosure (outdoor). Rated 240VAC (30A).

| General technical data | | |
|--|---|--|
| mechanical service life (operating cycles) typical | 10000 | |
| fastening method | SURFACE | |
| product function note | | |
| number of poles | 3 | |
| suitability for operation | DISCONNECTING MEAN FOR SERVICE ENTRANCE / LOADS | |
| Electricity | | |
| ampacity | 30 A | |
| supply voltage frequency rated value 50/60 Hz | Yes | |
| Environmental conditions | | |
| ambient temperature during operation maximum | 85 °C | |
| ambient temperature during operation minimum | -29 °C | |
| Model | | |
| product brand name | SIEMENS | |
| product sub brand name | VBII | |
| product type designation | HEAVY DUTY SWITCH | |
| type of electrical connection | MECHANICAL LUGS | |
| Mechanical Design | | |
| design of the housing | TYPE 3R | |
| design of the actuating element | SINGLE THROW | |
| material | STEEL | |
| General product approval | | |
| certificate of suitability | UL98 | |

| last modified: | 9/15/2021 (| |
|----------------|-------------|--|
| | | |