SIEMENS

Data sheet 1PH8087-1UF12-0LE1

	SIMOTICS M compact asynchronous motor 1500 r/min 3.7 kW 23.6 Nm 10 A 336 V 1750 r/min 4.3 kW 23.5 Nm 10 A 396 V 2000 r/min 4.9 kW 23.4 Nm 10 A 435 V 2200 r/min 5.3 kW 23 Nm 10 A 480 V forced ventilation; direction of air flow NDE--> DE; IP55 degree of protection Incremental encoder 20-bit Without commutation position (encoder IN20DQ) with DRIVE-CLiQ interface DESIGN IM B5 (IMV 1,IM V3) PLAIN SHAFT WITHOUT FITTED KEY; BEARING: PERFORMANCE, VIBRATION SEVERITY GRADE SPECIAL/B; SHAFT A. FLANGE ACCURACY GR. SPECIAL POWER CONNECTOR (ABOVE) CABLE ENTRY ON THE RIGHT SIGNAL CONNECTION D-END

Further information

Industry Online Support (Manuals, Catalogs, Certificates, FAQ, ...)
https://support.industry.siemens.com/cs/products?mfn=ps&lc=en-WW

Industry Mall (Online ordering system)
https://mall.industry.siemens.com

Subject to change without notice
© Copyright Siemens