SIEMENS

Data sheet 1PH8103-1DF02-2BD1

	SIMOTICS M compact asynchronous motor 1500 r/min 5.5 kW 35 Nm 13.5 A 368 V 1750 r/min 6.3 kW 34 Nm 13.1 A 412 V 2000 r/min 7 kW 33 Nm 12.7 A 460 V 2200 r/min 7.7 kW 33 Nm 12.7 A 480 V forced ventilation; direction of air flow DE--> NDE; IP55 degree of protection Incremental encoder 22-bit with commutation position (encoder IC22DQ) with DRIVE-CLiQ interface DESIGN IM B5 (IMV 1,IM V3) SHAFT WITH FITTED KEY HALF-KEY BALANCING BEARING: STANDARD WITH FIXED BEARING, VIBRATION SEVERITY GRADE: R/A, SHAFT AND FLANGE ACCURACY: R TERMINAL BOX (ABOVE) CABLE ENTRY ON THE D-END SIGNAL CONNECTION LEFT

Further information

Industry Online Support (Manuals, Catalogs, Certificates, FAQ, ...)
https://support.industry.siemens.com/cs/products?mfn=ps&lc=en-WW

Industry Mall (Online ordering system)
https://mall.industry.siemens.com

Subject to change without notice
© Copyright Siemens