SIEMENS

Data sheet 1PH8103-1DD03-2BC1

	SIMOTICS M compact asynchronous motor 1000 r/min 3.7 kW 35 Nm 10 A 333 V 1150 r/min 4.3 kW 36 Nm 10 A 380 V 1350 r/min 4.7 kW 33 Nm 9.7 A 423 V 1500 r/min 5.2 kW 33 Nm 9.7 A 470 V forced ventilation; direction of air flow DE--> NDE; IP55 degree of protection Incremental encoder 22-bit with commutation position (encoder IC22DQ) with DRIVE-CLiQ interface Design IM B35 (IM V15, (IM V35) SHAFT WITH FITTED KEY HALF-KEY BALANCING BEARING: STANDARD WITH FIXED BEARING, VIBRATION SEVERITY GRADE: R/A, SHAFT AND FLANGE ACCURACY: R TERMINAL BOX (ABOVE) CABLE ENTRY ON THE ND-END SIGNAL CONNECTION LEFT

Further information

Industry Online Support (Manuals, Catalogs, Certificates, FAQ, ...)
https://support.industry.siemens.com/cs/products?mfn=ps&lc=en-WW

Industry Mall (Online ordering system)
https://mall.industry.siemens.com

Subject to change without notice
© Copyright Siemens