SIEMENS

Data sheet 1PH8103-1DG02-0CE1

	SIMOTICS M compact asynchronous motor 2000 r/min 7 kW 33 Nm 17.5 A 345 V 2300 r/min 7.5 kW 31 Nm 17 A 382 V 2650 r/min 8 kW 29 Nm 16 A 434 V 2800 r/min 8.5 kW 29 Nm 16 A 455 V forced ventilation; direction of air flow DE--> NDE; IP55 degree of protection Incremental encoder 22-bit with commutation position (encoder IC22DQ) with DRIVE-CLiQ interface DESIGN IM B5 (IMV 1,IM V3) PLAIN SHAFT WITHOUT FITTED KEY; BEARING: STANDARD WITH FIXED BEARING, VIBRATION SEVERITY GRADE: S/A, SHAFT AND FLANGE ACCURACY: R POWER CONNECTOR (ABOVE) CABLE ENTRY ON THE RIGHT SIGNAL CONNECTION D-END

Further information

Industry Online Support (Manuals, Catalogs, Certificates, FAQ, ...)
https://support.industry.siemens.com/cs/products?mfn=ps&lc=en-WW

Industry Mall (Online ordering system)
https://mall.industry.siemens.com

Subject to change without notice
© Copyright Siemens