SIEMENS

Data sheet 1PH8103-1JD13-2GA2

	SIMOTICS M compact asynchronous motor 1000 r/min 3.7 kW 35 Nm 10 A 333 V 1150 r/min 4.3 kW 36 Nm 10 A 380 V 1350 r/min 4.7 kW 33 Nm 9.7 A 423 V 1500 r/min 5.2 kW 33 Nm 9.7 A 470 V forced ventilation; direction of air flow NDE --> DE; IP55 degree of protection Incremental encoder HTL 2048 S/R (encoder HTL2048S/R) With temperature sensor Pt1000 Design IM B35 (IM V15, (IM V35) SHAFT WITH FITTED KEY HALF-KEY BALANCING BEARING: STANDARD, VIBRATION SEVERITY GRADE: R/A, SHAFT AND FLANGE ACCURACY: R TERMINAL BOX (ABOVE) CABLE ENTRY ON THE RIGHT SIGNAL CONNECTION D-END

Further information

Industry Online Support (Manuals, Catalogs, Certificates, FAQ, ...)
https://support.industry.siemens.com/cs/products?mfn=ps&lc=en-WW

Industry Mall (Online ordering system)
https://mall.industry.siemens.com

Subject to change without notice
© Copyright Siemens