SIEMENS

Data sheet 1PH8105-1DF03-2BC1

	SIMOTICS M compact asynchronous motor 1500 r/min 7 kW 45 Nm 17.5 A 348 V 1750 r/min 8 kW 44 Nm 17.5 A 400 V 2000 r/min 9 kW 43 Nm 17 A 453 V 2200 r/min 9.9 kW 43 Nm 17 A 485 V forced ventilation; direction of air flow DE--> NDE; IP55 degree of protection Incremental encoder 22-bit with commutation position (encoder IC22DQ) with DRIVE-CLiQ interface Design IM B35 (IM V15, (IM V35) SHAFT WITH FITTED KEY HALF-KEY BALANCING BEARING: STANDARD WITH FIXED BEARING, VIBRATION SEVERITY GRADE: R/A, SHAFT AND FLANGE ACCURACY: R TERMINAL BOX (ABOVE) CABLE ENTRY ON THE ND-END SIGNAL CONNECTION LEFT

Further information

Industry Online Support (Manuals, Catalogs, Certificates, FAQ, ...)
https://support.industry.siemens.com/cs/products?mfn=ps&lc=en-WW

Industry Mall (Online ordering system)
https://mall.industry.siemens.com

Subject to change without notice
© Copyright Siemens