SIEMENS

Data sheet for SIMOTICS M-1PH8



Figure similar

Article No. : 1PH8131-2FF00-0QA1

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Engineering data

		P_N [kW]	M_N [Nm]	I_N [A]	U_N [V]	f_N [Hz]	n_N [rpm]	M_{max} [Nm]	I_{max} [A]	n_{max} [rpm]	M_0 [Nm]	I_0 [A]	η	cos φ	Iμ [A]
	ALM 400V	**18.0**	**98.0**	**29.0**	**415**	**58.3**	**1,750**	**220**	**74.0**	**4,500**	**105.0**	**30**	**0.947**	**0.000**	**0.0**
Y	BLM/SLM 400V	15.7	100.0	29.0	388	50.0	1,500	220	74.0	4,500	105.0	30	0.944	0.000	0.0
	ALM/BLM/SLM 480V	19.9	95.0	29.0	449	66.7	2,000	220	74.0	4,500	105.0	30	0.948	0.000	0.0

Mechanical data

Motor type	Permanent-magnet synchronous motor
Shaft height	132
Cooling	Forced ventilation DE -> NDE
Vibration severity grade	S/A
Shaft and flange accuracy	R
Degree of protection	IP55
Design acc. to Code I	IM B3 (IM V5, IM V6, IM B6, IM B7, IM B8)
Temperature monitoring	Pt1000 temperature sensor in the stator winding
Color	Standard (Anthracite RAL 7016)
Type of the bearing	Advanced Lifetime
Shaft end	Plain shaft
Encoder system	Absolut encoder 22 bit Singleturn + 12 bit Multiturn, max. encoder speed = 12000 rpm

Physical constants

Thermal time constant	10 min
Moment of inertia	446 kgcm²
Weight (approx.)	85 kg

Connection

Type of electrical connection	Terminal box
Position of the connection	NDE top
Power connection	right
Signal connection	DE
Terminal box designation	gk833

Cooling data and sound pressure level

Airflow, min.	0.09 m³/s
Sound pressure level LpA(1m) motor + external fan operation 50 HZ rated load, tolerance + 3dB	70 dB [1]
Air discharge	axial
Pressure drop	140 Pa

External fan

Max. power consumption

3 AC 400 V / 50 Hz (±10%)	0.10 A
3 AC 400 V / 60 Hz (±10%)	0.12 A
3 AC 480 V / 60 Hz (±10%)	0.12 A

[1] at a rated frequency of 4 kHz and a speed range of up to 5000 rpm