SIEMENS

Data sheet for SIMOTICS M-1PH8



Figure similar

Article No. : 1PH8137-1DS00-1BB1

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Engineering data

		P_N [kW]	M_N [Nm]	I_N [A]	U_N [V]	f_N [Hz]	n_N [rpm]	M_{max} [Nm]	I_{max} [A]	n_{max} [rpm]	M_0 [Nm]	I_0 [A]	η	cos φ	Iμ [A]
Y	**ALM 400V**	**29.0**	**138.0**	**56.0**	**400**	**68.0**	**2,000**	**320**	**130.0**	**8,000**	**185.0**	**68**	**0.931**	**0.850**	**22.7**
	BLM/SLM 400V	22.0	140.0	56.0	308	51.3	1,500	320	130.0	8,000	185.0	68	0.902	0.840	24.2
	ALM 480V	37.0	118.0	54.0	510	101.5	3,000	320	130.0	8,000	185.0	68	0.940	0.890	17.4
	BLM/SLM 480V	36.0	138.0	50.0	460	84.9	2,500	320	130.0	8,000	185.0	68	0.951	0.890	17.4
Δ	**ALM 400V**	**27.5**	**53.0**	**56.0**	**425**	**167.5**	**5,000**	**160**	**160.0**	**8,000**	**105.0**	**87**	**0.919**	**0.830**	**22.5**
	BLM/SLM 400V	22.0	53.0	55.0	383	134.0	4,000	160	160.0	8,000	105.0	87	0.907	0.760	27.6
	ALM 480V	37.0	50.0	53.0	510	235.0	7,000	160	160.0	8,000	105.0	87	0.920	0.870	20.0
	BLM/SLM 480V	33.0	53.0	55.0	460	201.0	6,000	160	160.0	8,000	105.0	87	0.942	0.870	20.0

Mechanical data

Motor type	Squirrel cage asynchronous motor
Shaft height	132
Cooling	Forced ventilation DE -> NDE
Vibration severity grade	R/A
Shaft and flange accuracy	R
Degree of protection	IP55
Design acc. to Code I	IM B3 (IM V5, IM V6, IM B6, IM B7, IM B8)
Temperature monitoring	Pt1000 temperature sensor in the stator winding
Color	Standard (Anthracite RAL 7016)
Type of the bearing	Standard with fixed bearing
Shaft end	Feather key with full key balancing
Encoder system	Incremental encoder 22 bit with commutation position 11 bit, max. encoder speed = 12000 rpm

Physical constants

Thermal time constant	30 min
Moment of inertia	1,090 kgcm²
Weight (approx.)	141 kg

Connection

Type of electrical connection	Terminal box
Position of the connection	NDE top
Power connection	left
Signal connection	DE
Terminal box designation	gk846

Cooling data and sound pressure level

Airflow, min.	0.09 m³/s
Sound pressure level LpA(1m) motor + external fan operation 50 HZ rated load, tolerance + 3dB	70 dB [1]
Air discharge	axial
Pressure drop	140 Pa

External fan

Max. power consumption

3 AC 400 V / 50 Hz (±10%)	0.10 A
3 AC 400 V / 60 Hz (±10%)	0.12 A
3 AC 480 V / 60 Hz (±10%)	0.12 A

[1] at a rated frequency of 4 kHz and a speed range of up to 5000 rpm