SIEMENS

Data sheet 1PH8105-1HF00-1BA2

	SIMOTICS M compact asynchronous motor 1500 r/min 7 kW 45 Nm 17.5 A 348 V 1750 r/min 8 kW 44 Nm 17.5 A 400 V 2000 r/min 9 kW 43 Nm 17 A 453 V 2200 r/min 9.9 kW 43 Nm 17 A 485 V forced ventilation; direction of air flow DE --> NDE; IP55 degree of protection Incremental encoder HTL 1024 S/R (encoder HTL1024S/R) With temperature sensor Pt1000 DESIGN IM B3 (IM V5, IM V6) SHAFT WITH FITTED KEY FULL-KEY BALANCING BEARING: STANDARD WITH FIXED BEARING, VIBRATION SEVERITY GRADE: R/A, SHAFT AND FLANGE ACCURACY: R TERMINAL BOX (ABOVE) CABLE ENTRY ON THE RIGHT SIGNAL CONNECTION D-END

Further information

Industry Online Support (Manuals, Catalogs, Certificates, FAQ, ...)
https://support.industry.siemens.com/cs/products?mfn=ps&lc=en-WW

Industry Mall (Online ordering system)
https://mall.industry.siemens.com

Subject to change without notice
© Copyright Siemens