SIEMENS

Data sheet 1PH8105-1CS00-0LA2

	SIMOTICS M compact asynchronous motor Y2000RPM, 10.0 kW, 48 Nm, 23 A, 366 V D5000RPM, 9.3 kW, 18 Nm, 24 A, 398 V Y1500RPM, 7.5 kW, 48 Nm, 23 A, 285 V forced ventilation; direction of air flow DE --> NDE; IP55 degree of protection Incremental encoder sin/cos 1 Vpp 256 S/R without C and D track (encoder IN256S/R) With temperature sensor Pt1000 DESIGN IM B3 (IM V5, IM V6) PLAIN SHAFT WITHOUT FITTED KEY; BEARING: PERFORMANCE, VIBRATION SEVERITY GRADE SPECIAL/B; SHAFT A. FLANGE ACCURACY GR. SPECIAL TERMINAL BOX (ABOVE) CABLE ENTRY ON THE RIGHT SIGNAL CONNECTION D-END

Further information

Industry Online Support (Manuals, Catalogs, Certificates, FAQ, ...)
https://support.industry.siemens.com/cs/products?mfn=ps&lc=en-WW

Industry Mall (Online ordering system)
https://mall.industry.siemens.com

Subject to change without notice
© Copyright Siemens