

Representative Image

Catalog No. U055C033

Description: 70A SURFACE UNMTRD 50/20GFCI

UPC No 784567570533

Home > Temporary Power > Temporary Power

Midwest Electric's Temporary Power and Power Outlets are a means of providing power required by various construction trades, residential sites, and mobile electrical applications. Temporary Power and Power Outlets offer one or more receptacles, with or without overcurrent protection, disconnecting, metering, and/or pedestal mounting functions, in a single enclosure of G-90 zinc-coated steel. The NEMA 3R rainproof enclosure is lockable and engineered to provide maximum protection against weather, vandalism, and normal field use.

Descriptors

Category	Temporary Power

Specifications

Mounting	Surface
Heads	1
Metering	Unmetered
Receptacles	14-50R 5-20R2GFCI
Feed	Overhead
AIC	10,000
Amps	70.0 A
Cabinet Size	6 X 14
Circuit Protection	Yes
Hub Provision	Yes
Installed Breaker	GFI250 CB120
Load Center	LC33N7
Loop Feed	No
Phase	1
Suitable for Service Equipment	Yes
Unit Weight	10.0 lb
Volts	120/240

Classifications

Standard Package	4
Stock Class Code	Stock

Approvals

Certification	UL/CUL

Publications

Title	Publication No.	Publication Type
Storm Season Brochure This brochure highlights the most popular products sold during storm season.	MET1005	Brochures
Storm Season Brochure This brochure highlights the most popular products sold during storm season.	005	Brochures
Temporary Power Brochure 6 pages. MET-019 Rev. B.	MET-019A	Brochures

Additional Documentation: Visit our Publication Library to find technical documentation, time current curves, CSI Specifications and promotional literature.