

SKU: CLNB-2-14-58-4

UPC: 0783669660555

Features & Benefits:

Description: Surecrimp Copper Compression Lug, Conductor Size 2, 2 Holes, 1/4in Bolt Size, 5/8in Hole Spacing, Long Barrel, No Sight Window, 45° Bent Tang, Tin Plated, UL, CSA

Specs

Additional Class Attributes

Barrel Marking	Hard
Barrel Type	Long
Connecting Angle	45°
Connection	Compression
Contains DE-OX®	Yes
Flared End	No
ILSCOs Die Catalog Number	ILD-33
ILSCOs Die Index Number	I-33
Mounting Hole Type	Thru
Narrow Tang	No
Number of Mounting Holes	2
Sight Window	No
Slotted	No
Tang End Shape	Square
Undrilled	No

Dimensions

Barrel Length (IN)	1.125
Barrel Length (mm)	28.575
Dimension G (IN)	0.321
Dimension G (mm)	8.1534
Height (IN)	1.38
Height BX (IN)	1.875
Height (mm)	35.052
Inside Diameter (IN)	0.312
Inside Diameter (mm)	7.9248
Length (IN)	2.564
Length (mm)	65.1256
Mounting Hole Diameter (IN)	0.281
Mounting Hole Diameter (mm)	7.1374
Mounting Hole Spacing (IN)	0.625
Mounting Hole Spacing (mm)	15.875
Outside Diameter (IN)	0.421
Outside Diameter (mm)	10.6934
Strip Length (mm)	30.1625
Tang Length (IN)	1.437
Tang Length (mm)	36.4998
Tang Thickness (IN)	0.109
Tang Thickness (mm)	2.7686

Tang Width (IN)	0.599
Tang Width (mm)	15.2146
Weight (LB)	0.0551599337803659
Weight BX (LB)	2.35
Width (IN)	0.599
Width BX (IN)	4.625
Width (mm)	15.2146

Conductor Ranges

Conductor Range AL Stranded (Primary, run, main, line)	NA
Conductor Range CU Solid (Primary, run, main, line)	2 Sol
Conductor Range CU Stranded (Primary, run, main, line)	2 Str
Conductor Range AL Solid (Primary, run, main, line)	NA
Expanded Conductor Range	2 Str - 6 Str
Flex Conductor Range	4 G,H,I,K,M,DLO

Material and Finish

Conductor Material	Copper
Connector Finish	Tin
Insulation	NA
Material	Copper

Additional Technical Specifications

Conductor Type	Flex

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 25
Direct Burial	Yes
Dual Rated	No
NEMA Code	S-588-3
UPC Code	78366966055

Bolt and Screw Sizes

Mounting Bolt/Stud Size	1/4

Testing Standards

CSA File Number	LR-29601
CSA Standard	C22.2 No. 65-03
NEBS Rating	Level 3
Prop65 Compliance	This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation
UL Control Number	453G
UL / CULUS Specification	UL 467 Listed
UL File Number	E6207

Environment and Temperature

Temperature Rating	90°C

Color

Color	Silver
Color Code	Brown

Voltage

Voltage Rating	35 kV