

**SKU:** CLNB-250-38-134-9

**UPC:** 0783669674729

**Features & Benefits:**

**Description:**Surecrimp Copper Compression Lug, Conductor Size 250, 2 Holes, 3/8in Bolt Size, 1-3/4in Hole Spacing, Long Barrel, No Sight Window, 90° Bent Tang, Tin Plated, UL, CSA

# Specs

## *Additional Class Attributes*

| | |
|---|---|
| **Barrel Marking** | Hard |
| **Barrel Type** | Long |
| **Connecting Angle** | 90° |
| **Connection** | Compression |
| **Contains DE-OX®** | Yes |
| **Flared End** | No |
| **ILSCOs Die Catalog Number** | ILD-62 |
| **ILSCOs Die Index Number** | I-62 |
| **Mounting Hole Type** | Thru |
| **Narrow Tang** | No |
| **Number of Mounting Holes** | 2 |
| **Sight Window** | No |
| **Slotted** | No |
| **Tang End Shape** | Square |
| **Undrilled** | No |

## *Dimensions*

| | |
|---|---|
| **Barrel Length (IN)** | 1.688 |
| **Barrel Length (mm)** | 42.8752 |
| **Dimension G (IN)** | 0.414 |
| **Dimension G (mm)** | 10.5156 |
| **Height (IN)** | 2.497 |
| **Height BX (IN)** | 2 |
| **Height (mm)** | 63.4238 |
| **Inside Diameter (IN)** | 0.593 |
| **Inside Diameter (mm)** | 15.0622 |
| **Length (IN)** | 3.511 |
| **Length (mm)** | 89.1794 |
| **Mounting Bolt/Stud Size (mm)** | 965.2 |
| **Mounting Hole Diameter (IN)** | 0.406 |
| **Mounting Hole Diameter (mm)** | 10.3124 |
| **Mounting Hole Spacing (IN)** | 1.75 |
| **Mounting Hole Spacing (mm)** | 44.45 |
| **Outside Diameter (IN)** | 0.751 |
| **Outside Diameter (mm)** | 19.0754 |
| **Strip Length (mm)** | 44.45 |
| **Tang Length (IN)** | 2.625 |
| **Tang Length (mm)** | 66.675 |
| **Tang Thickness (IN)** | 0.157 |

| | |
|---|---|
| **Tang Thickness (mm)** | 3.9878 |
| **Tang Width (IN)** | 1.088 |
| **Tang Width (mm)** | 27.6352 |
| **Weight (LB)** | 0.260538521072411 |
| **Weight BX (LB)** | 2.81 |
| **Width (IN)** | 1.088 |
| **Width BX (IN)** | 6.188 |
| **Width (mm)** | 27.6352 |

## Conductor Ranges

| | |
|---|---|
| **Conductor Range AL Stranded (Primary, run, main, line)** | NA |
| **Conductor Range CU Solid (Primary, run, main, line)** | NA |
| **Conductor Range CU Stranded (Primary, run, main, line)** | 250 kcmil |
| **Conductor Range AL Solid (Primary, run, main, line)** | NA |
| **Expanded Conductor Range** | 250 kcmil - 1/0 Str |
| **Flex Conductor Range** | 4/0 G,H,I,K,M,DLO |

## Material and Finish

| | |
|---|---|
| **Conductor Material** | Copper |
| **Connector Finish** | Tin |
| **Insulation** | NA |
| **Material** | Copper |

## Additional Technical Specifications

| | |
|---|---|
| **Conductor Type** | Stranded |

## General

| | |
|---|---|
| **Bag Quantity** | 1 |
| **Carton Quantity Description** | STD PACK QTY 10 |
| **Direct Burial** | Yes |
| **Dual Rated** | No |
| **NEMA Code** | S-588-3 |
| **UPC Code** | 78366967472 |

## Bolt and Screw Sizes

| | |
|---|---|
| **Mounting Bolt/Stud Size** | 3/8 |

## Testing Standards

| | |
|---|---|
| **CSA File Number** | LR-29601 |
| **CSA Standard** | C22.2 No. 65-03 |
| **NEBS Rating** | Level 3 |
| **Prop65 Compliance** | This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation |
| **UL Control Number** | 453G |
| **UL / CULUS Specification** | UL 486A/B Listed |
| **UL File Number** | E6207 |

## Environment and Temperature

| | |
|---|---|
| **Temperature Rating** | 90°C |

## Color

| | |
|---|---|
| **Color** | Silver |
| **Color Code** | Yellow |

## Voltage

| | |
|---|---|
| **Voltage Rating** | 35 kV |