

SKU: CSWN-2/0-38

UPC: 0783669685473

Features & Benefits:

Description: Surecrimp Copper Compression Lug, Conductor Size 2/0, 1 Hole, 3/8in Bolt Size, Standard Barrel, Sight Window, Narrow Tang, Tin Plated, UL, CSA

Specs

Additional Class Attributes

Barrel Marking	Ink
Barrel Type	Standard
Connecting Angle	180°
Connection	Compression
Contains DE-OX®	Yes
Flared End	No
ILSCOs Die Catalog Number	ILD-45
ILSCOs Die Index Number	I-45
Mounting Hole Type	Thru
Narrow Tang	Yes
Number of Mounting Holes	1
Sight Window	Yes
Slotted	No
Tang End Shape	Square
Undrilled	No

Dimensions

Barrel Length (IN)	0.75
Barrel Length (mm)	19.05
Dimension G (IN)	0.414
Dimension G (mm)	10.5156
Height (IN)	0.597
Height BX (IN)	2.25
Height (mm)	15.1638
Inside Diameter (IN)	0.437
Inside Diameter (mm)	11.0998
Length (IN)	2.021
Length (mm)	51.3334
Mounting Bolt/Stud Size (mm)	965.2
Mounting Hole Diameter (IN)	0.406
Mounting Hole Diameter (mm)	10.3124
Mounting Hole Spacing (mm)	0
Outside Diameter (IN)	0.562
Outside Diameter (mm)	14.2748
Strip Length (mm)	20.6375
Tang Length (IN)	0.875
Tang Length (mm)	22.225
Tang Thickness (IN)	0.16
Tang Thickness (mm)	4.064

Tang Width (IN)	0.547
Tang Width (mm)	13.8938
Weight (LB)	0.0505476930299976
Weight BX (LB)	1.4344
Width (IN)	0.547
Width BX (IN)	5
Width (mm)	13.8938

Conductor Ranges

Conductor Range AL Stranded (Primary, run, main, line)	NA
Conductor Range CU Solid (Primary, run, main, line)	NA
Conductor Range CU Stranded (Primary, run, main, line)	2/0 Str
Conductor Range AL Solid (Primary, run, main, line)	NA
Expanded Conductor Range	2/0 Str - 4 Str
Flex Conductor Range	1/0 G,H,I,K,M,DLO

Material and Finish

Conductor Material	Copper
Connector Finish	Tin
Insulation	NA
Material	Copper

Additional Technical Specifications

Conductor Type	Flex

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 10
Direct Burial	Yes
Dual Rated	No
NEMA Code	S-588-3
UPC Code	78366968547

Bolt and Screw Sizes

Mounting Bolt/Stud Size	3/8

Testing Standards

CSA File Number	LR-29601
CSA Standard	C22.2 No. 65-03
NEBS Rating	Level 3
Prop65 Compliance	This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation
UL Control Number	453G
UL / CULUS Specification	UL 486A/B Listed
UL File Number	E6207

Environment and Temperature

Temperature Rating	90°C

Color

Color	Silver
Color Code	Black

Voltage

Voltage Rating	35 kV

ILSCO
4730 MADISON ROAD
CINCINNATI, OH 45227
513-533-6200
800-776-9775