

SKU: CLNU-700-4

UPC: 0783669685121

Features & Benefits:

Description: Surecrimp Copper Compression Lug, Conductor Size 700, No Hole, 45° Bent Tang, Long Barrel, No Sight Window, Tin Plated, UL, CSA

Specs

Additional Class Attributes

Barrel Marking	Ink
Barrel Type	Long
Connecting Angle	180°
Connection	Compression
Contains DE-OX®	No
Flared End	No
ILSCOs Die Catalog Number	ILD-99
ILSCOs Die Index Number	I-99
Mounting Hole Type	NA
Narrow Tang	No
Number of Mounting Holes	1
Sight Window	No
Slotted	No
Tang End Shape	Square
Undrilled	Yes

Dimensions

Barrel Length (IN)	2.687
Barrel Length (mm)	68.2498
Dimension G (mm)	0
Height (IN)	3.561
Height BX (IN)	2
Height (mm)	90.4494
Inside Diameter (IN)	0.991
Inside Diameter (mm)	25.1714
Length (IN)	5.82
Length (mm)	147.828
Mounting Hole Diameter (mm)	0
Mounting Hole Spacing (mm)	0
Outside Diameter (IN)	1.249
Outside Diameter (mm)	31.7246
Strip Length (mm)	69.8246
Tang Length (IN)	3
Tang Length (mm)	76.2
Tang Thickness (IN)	0.259
Tang Thickness (mm)	6.5786
Tang Width (IN)	1.816
Tang Width (mm)	46.1264
Weight (LB)	0.989071844904817
Weight BX (LB)	6.1759
Width (IN)	1.816
Width BX (IN)	6.188

Width (mm)	46.1264

Conductor Ranges

Conductor Range AL Stranded (Primary, run, main, line)	NA
Conductor Range CU Solid (Primary, run, main, line)	NA
Conductor Range CU Stranded (Primary, run, main, line)	700 kcmil
Conductor Range AL Solid (Primary, run, main, line)	NA
Expanded Conductor Range	700 kcmil - 350 kcmil
Flex Conductor Range	500 G,H,I, K,M 535.3 DLO

Material and Finish

Conductor Material	Copper
Connector Finish	Tin
Insulation	NA
Material	Copper

Additional Technical Specifications

Conductor Type	Stranded

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 6
Direct Burial	No
Dual Rated	No
NEMA Code	S-588-3
UPC Code	78366968512

Bolt and Screw Sizes

Mounting Bolt/Stud Size	NA

Testing Standards

CSA File Number	LR-29601
CSA Standard	C22.2 No. 65-03
NEBS Rating	Level 3
Prop65 Compliance	This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation
UL Control Number	453G
UL / CULUS Specification	UL 486A/B Listed
UL File Number	E6207

Environment and Temperature

Temperature Rating	90°C

Color

Color	Silver
Color Code	Pink

Voltage

Voltage Rating	35 kV

ILSCO
4730 MADISON ROAD
CINCINNATI, OH 45227
513-533-6200
800-776-9775