

SKU: PBTD-7-250-M

UPC: 0783669000924

Features & Benefits:

Description: Nimbus Insulated Aluminum Multi-Tap Connector, Conductor Range 250-6, 7 Ports, Dual Sided Entry, Mountable, Tin Plated, UL, CSA



Specs

Additional Class Attributes

Connection	Mechanical
Contains DE-OX®	Yes
Mounting Hole Type	Thru
Number of Conductors	7
Number of Mounting Holes	2
Number of Poles	1
Number of Ports / Wireways	7
Number of Usable Ports	7
Replacement Part(s)	PORTPLUG-250, SCREWCAP-250

Dimensions

Drive Size Main	5/16
Drive Type Main	Internal Hex
Height (IN)	2.197
Height BX (IN)	3.75
Height (mm)	55.8038
Length (IN)	8.604
Length (mm)	218.5416
Max Insulation OD (IN)	0.75
Max Insulation OD (mm)	19.05
Mounting Hole Diameter (IN)	0.266
Mounting Hole Spacing (IN)	7.174
Mounting Hole Spacing (mm)	182.2196
Weight (LB)	1.144
Weight BX (LB)	3.7455
Width (IN)	2.318
Width BX (IN)	6.375
Width (mm)	58.8772

Material and Finish

Conductor Material	Aluminum
Connector Finish	Tin
Insulation	Plastisol
Material	Aluminum
Wire Binding Hardware Finish	Tin
Wire Binding Hardware Material	Aluminum

Additional Technical Specifications

Conductor Type	Stranded
----------------	----------

Bolt and Screw Sizes

Number of Wire Binding Screws per Port	1
Wire Binding Screw Size	9/16
Wire Binding Torque	275

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 3
Dual Rated	Yes
NEMA Code	S-588-4
UPC Code	78366900092

Testing Standards

CSA File Number	LR-29601
CSA Standard	C22.2 No. 65-03
Prop65 Compliance	WARNING: Cancer and Reproductive Harm - www.P65warnings.ca.gov
UL Control Number	453G
UL / CULUS Specification	UL 486A/B Listed
UL File Number	E6207

Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)	NA
Conductor Range AL Stranded (Primary, run, main, line)	250 kcmil - 6 Str
Conductor Range AL Stranded (Secondary, tap, load)	NA
Conductor Range CU Solid (Primary, run, main, line)	NA
Conductor Range CU Solid (Secondary, tap, load)	NA
Conductor Range CU Stranded (Primary, run, main, line)	250 kcmil - 6 Str
Conductor Range CU Stranded (Secondary, tap, load)	NA
Conductor Range AL Solid (Primary, run, main, line)	NA
Flex Conductor Range	NA

Voltage

Voltage Rating	600 V
----------------	-------

Color

Cap Color Main	Black
Cap Color Tap	Black
Color	Black

Environment and Temperature

Environmental Conditions	Cold temperature rated to -45°C
--------------------------	---------------------------------

Flammability Rating
Temperature Rating

Insulation rated per UL 94
90°C