



SKU: SK-10

UPC: 0783669818987

Features & Benefits:

Description: Copper Split Bolt, Conductor Range for Equal Main & Tap 10-16, Tin Plated, UL, CSA

Specs

Additional Class Attributes

Connection	Mechanical
Number of Conductors	1
Number of Poles	1

Dimensions

Drive Size Main	1/2
Drive Type Main	External Hex
Height (IN)	0.73
Height BX (IN)	2.25
Height (mm)	18.542
Length (IN)	0.577
Length (mm)	14.6558
Weight (LB)	0.00829654342387664
Weight BX (LB)	2.9
Width (IN)	0.577
Width BX (IN)	5
Width (mm)	14.6558
Wire Diameter Range Primary (IN)	0.057 - 0.116

Material and Finish

Conductor Material	Copper
Connector Finish	Tin
Insulation	NA
Material	Copper
Wire Binding Hardware Finish	Tin
Wire Binding Hardware Material	Copper

Additional Technical Specifications

Conductor Type	Solid
----------------	-------

Bolt and Screw Sizes

Number of Wire Binding Screws per Port	1
Wire Binding Screw Size	NA

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 100
Direct Burial	No
Dual Rated	No
NEMA Code	S-588-4
UPC Code	78366981898

Testing Standards

CSA File Number	LR-701570
CSA Standard	C22.2 No. 65
Prop65 Compliance	WARNING: Cancer and Reproductive Harm - www.P65warnings.ca.gov
RUS Listed	Yes
UL Control Number	460C
UL / CULUS Specification	UL 486A/B Listed
UL File Number	E6207

Environment and Temperature

Temperature Rating	90°C
--------------------	------

Color

Color	Silver
-------	--------

Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)	NA
Conductor Range AL Stranded (Primary, run, main, line)	NA
Conductor Range AL Stranded (Secondary, tap, load)	NA
Conductor Range CU Solid (Primary, run, main, line)	10 Sol - 16 Sol
Conductor Range CU Solid (Secondary, tap, load)	10 Sol - 16 Sol
Conductor Range CU Stranded (Primary, run, main, line)	10 Str - 16 Str
Conductor Range CU Stranded (Secondary, tap, load)	10 Str - 16 Str
Conductor Range for Equal Run & Tap ACSR	NA
Conductor Range for Equal Run & Tap Str	10 Str - 16 Str
Conductor Range for Equal Run & Tap Sol	10 Sol - 14 Sol
Conductor Range for Minimum Tap with Maximum Run	16 Str
Conductor Range AL Solid (Primary, run, main, line)	10 Sol - 16 Sol

Voltage

Voltage Rating	35 kV
----------------	-------