



## AMHMI206CCL

20"x16" HMI Cover Kit with hinged clear cover and stainless-steel snap latch

**Availability:**

Delivery may take longer than normal. For up-to-date delivery on this product, please contact us at 1-800-722-2679 or [sales@alliedmoulded.com](mailto:sales@alliedmoulded.com)

**Cover Type:** Clear Polycarbonate

**Closure Type:** Metal Snap Latch

**Mounting Description:** 18 Screws

**Box Features:**

**Installation Type:**

**Height:** 19.85 in

**Width:** 16.07 in

**Depth:** 0.96 in

**Usable Depth:** 2.17 in

**Volume:** 692 cu in

## Product Info

**UPC:** 85339978466

**UNSPSC:** 39121302

**Carton Quantity:** 1

**Carton Weight:** 8 lbs

**Carton Length:** 5 in

**Carton Width:** 20 in

**Carton Height:** 22 in

**Country of Origin:** United States of America

**Color:** Gray (RAL 7035) with clear cover

**Material:** Polycarbonate frame and cover

**Additional Materials:** 319 stainless steel external hardware,

## Features:

Non-corrosive, non-conductive, light weight with lower installation cost and longer life cycle cost compared to steel. Rigid design with a gasket system encased in a continuous channel on the cover and frame. Open back frame design with an opening size of 14.71" x 18.49" and is a UL recognized component for use with NEMA 4X enclosures.\*Will fit Allied Moulded enclosure sizes 24 x 24 and larger.

## Standards:


Meets Requirements: ANSI/UL50, ANSI/UL50E, and ANSI/UL508A; [File No. E487574](#)

UL® listed and recognized component for use with CSA® listed enclosure products Types 1, 2, 3, 3R, 4, 4X, 12 and 13.

Complies With:

1. EN / IEC 60204-1 and 60529 Type IP66
2. RoHS directive



 **WARNING** - PROP 65  
[Click here for more information!](#)