

McGill™ 5000 Series Industrial Extension Lights

Thermoplastic Handle With or Without Receptacle

NEC/CEC:
Listed for Ordinary (Unclassified) Locations

NEC:
Meets OSHA requirements

Features

- Industrial-duty extension lights resist impact, abrasion and oil.
- Yellow handles with receptacle, yellow cords, and grounded cages enhance safety, while easy-open cages speed relamping.
- All-weather cords have molded plugs for durability.
- Cages feature rotating hooks and NO-ROL design for accurate light positioning.
- Accommodates up to 200 Watt rough service bulbs.
- Meets NEC requirements for power tool grounding.

Standard Materials

- Cords: 16/3-SJTW thermoplastic
- Cages: 10 gauge steel

Standard Finish

- Cages: zinc plated, chrome finish

Options

- NEC Version: 13 Amp, 125 Vac receptacle rating.
- CEC Version 15 Amp, 120 Vac receptacle rating.

NEC/CEC Certification and Compliances ①

- UL Listed (with cord): E59071
- UL Listed (without cord): E59054
- UL Standard: 153
- CSA Certified (with cord): LL89639
- CSA Certified (without cord): LL56247
- CSA Standard: C22.2 No. 12

	Amp /Vac	with out Cord	Catalog Numbers	
			with 7.6 m (25') 16/3-SJTW Cord	with 15.2 m (50') 16/3-SJTW Cord
Closed-End Extension Lights				
Handle and cage	13 Amp/ 125 Vac	5000-G	5025-G	5050-G
Handle and cage	15 Amp/ 120 Vac	C5000-G ②	C5025-G ②	C5050-G ②
Handle and cage with reflector	13 Amp/ 125 Vac	5000-RG	5025-RG	5050-RG
Handle and cage with reflector	15 Amp/ 120 Vac	C5000-RG ②	C5025-RG ②	C5050-RG ②
Handle and cage, no receptacle	13 Amp/ 125 Vac	5000-GN	5025-GN	5050-GN
Handle and cage, no receptacle	15 Amp/ 120 Vac	C5000-GN ②	C5025-GN ②	C5050-GN ②
Handle and cage with reflector, no receptacle	13 Amp/ 125 Vac	5000-RGN	5025-RGN	5050-RGN
Handle and cage with reflector, no receptacle	15 Amp/ 120 Vac	C5000-RGN ②	C5025-RGN ②	C5050-RGN ②
Handle and non-metallic cage	13 Amp/ 125 Vac	—	5999-GH	—
Handle and non-metallic cage	15 Amp/ 120 Vac	—	C5999-GH ②	—
Handle and non-metallic cage with reflector	13 Amp/ 125 Vac	—	5999-RGH	—
			Catalog Number	
			With Out Reflector	With Reflector
Cages				
Wire cage			8171	8170
Vinyl insulated metal cage (100 Watt A-21)			08171	08170
Non-metallic cage (100 Watt A-19)			—	8224
			Catalog Number	
			With Out Switch	
Handles and Sockets				
Handle and socket for 5000			0877	
Handle and socket for 5000-N			0877-N	
Socket for 5000 and 5000-N			00868	

① 100 Watt Maximum for UL Listing and CSA Certification.

② Certified to meet the Canadian Electrical Code (CEC) only.