SIEMENS

Data sheet for SIMOTICS M-1PH8



Figure similar

Article No. : **1PH8165-1HB03-2FB2**

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Engineering data

		P_N [kW]	M_N [Nm]	I_N [A]	U_N [V]	f_N [Hz]	n_N [rpm]	M_{max} [Nm]	I_{max} [A]	n_{max} [rpm]	M_0 [Nm]	I_0 [A]	η	cos φ	Iμ [A]
Y	**ALM 400V**	**16.0**	**306.0**	**36.0**	**365**	**17.5**	**500**	**610**	**75.0**	**5,300**	**329.0**	**37**	**0.830**	**0.850**	**14.8**
	BLM/SLM 400V	13.0	310.0	36.0	300	14.1	400	610	75.0	5,300	329.0	37	0.826	0.860	14.9
	ALM 480V	22.0	300.0	35.0	475	24.3	700	610	75.0	5,300	329.0	37	0.900	0.880	12.0
	BLM/SLM 480V	19.0	302.0	35.0	420	20.8	600	610	75.0	5,300	329.0	37	0.850	0.880	12.0

Mechanical data

Motor type	Squirrel cage asynchronous motor
Shaft height	160
Cooling	Forced ventilation DE -> NDE
Vibration severity grade	R/A
Shaft and flange accuracy	R
Degree of protection	IP55
Design acc. to Code I	IM B35 (IM V15, IM V35)
Temperature monitoring	Pt1000 temperature sensor in the stator winding
Color	Standard (Anthracite RAL 7016)
Type of the bearing	Increased cantilever forces
Shaft end	Feather key with half key balancing
Encoder system	Incremental encoder HTL 1024 S/R, max. encoder speed = 9000 rpm

Physical constants

Thermal time constant	35 min
Moment of inertia	2,320 kgcm²
Weight (approx.)	230 kg

Connection

Type of electrical connection	Terminal box
Position of the connection	NDE top
Power connection	left
Signal connection	DE
Terminal box designation	gk863

Cooling data and sound pressure level

Airflow, min.	0.16 m³/s
Sound pressure level LpA(1m) motor + external fan operation 50 HZ rated load, tolerance + 3dB	73 dB [1]
Air discharge	axial
Pressure drop	200 Pa

External fan

Max. power consumption

3 AC 400 V / 50 Hz (±10%)	0.16 A
3 AC 400 V / 60 Hz (±10%)	0.21 A
3 AC 480 V / 60 Hz (±10%)	0.21 A

[1] at a rated frequency of 4 kHz and a speed range of up to 5000 rpm