SIEMENS

Data sheet for SIMOTICS M-1PH8



Figure similar

Article No. : **1PH8226-1DF00-1AA1**

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Engineering data

		P_N [kW]	M_N [Nm]	I_N [A]	U_N [V]	f_N [Hz]	n_N [rpm]	M_{max} [Nm]	I_{max} [A]	n_{max} [rpm]	M_0 [Nm]	I_0 [A]	η	cos φ	Iμ [A]
Y	**ALM 400V**	**135.0**	**737.0**	**250.0**	**395**	**58.8**	**1,750**	**1,850**	**570.0**	**4,500**	**737.0**	**250**	**0.960**	**0.830**	**119.0**
	BLM/SLM 400V	130.0	828.0	270.0	340	50.5	1,500	1,850	570.0	4,500	828.0	270	0.957	0.850	119.0
	ALM 480V	130.0	564.0	205.0	500	73.7	2,200	1,850	570.0	4,500	828.0	205	0.958	0.760	123.0
	BLM/SLM 480V	153.0	731.0	245.0	450	67.1	2,000	1,850	570.0	4,500	731.0	245	0.961	0.830	119.0

Mechanical data

Motor type	Squirrel cage asynchronous motor
Shaft height	225
Cooling	Forced ventilation DE -> NDE
Vibration severity grade	A
Shaft and flange accuracy	N
Degree of protection	IP55
Design acc. to Code I	IM B3 (IM B6, IM B7, IM B8, IM V6)
Temperature monitoring	Pt1000 temperature sensor in the stator winding
Color	Standard (Anthracite RAL 7016)
Type of the bearing	Standard
Shaft end	Feather key with full key balancing
Encoder system	Incremental encoder 22 bit with commutation position 11 bit, max. encoder speed = 12000 rpm

Physical constants

Thermal time constant	52 min
Moment of inertia	19,300 kgcm²
Weight (approx.)	740 kg

Connection

Type of electrical connection	Terminal box
Position of the connection	NDE top
Power connection	right
Signal connection	DE
Terminal box designation	1XB7422-P06

Cooling data and sound pressure level

Airflow, min.	0.31 m³/s
Sound pressure level LpA(1m) motor + external fan operation 50 HZ rated load, tolerance + 3dB	73 dB [1]
Air discharge	axial
Pressure drop	650 Pa

External fan

Max. power consumption

1 AC 200 ... 277 V (±10%) 50/60 Hz ±10%	2.0 ... 2.3 A

[1] at a rated frequency of 2 kHz and a speed range of up to 3500 rpm