



Siemens Low Voltage Circuit Protection Heavy Duty Safety Switch. 3-Pole 3-Fuse Fused in a type 3R enclosure (outdoor). Rated 600VAC (100A).

| General technical data                             |   |
|--|---|
| mechanical service life (operating cycles) typical | 10000   |
| fastening method                                   | SURFACE   |
| product function note                              |   |
| number of poles                                    | 3   |
| suitability for operation                          | DISCONNECTING MEAN FOR LOADS / SERVICE ENTRANCE (IN US) |
| Electricity  |   |
| ampacity   | 100 A   |
| supply voltage frequency rated value 50/60 Hz      | Yes   |
| Environmental conditions                           |   |
| ambient temperature during operation maximum       | 85 °C   |
| ambient temperature during operation minimum       | -29 °C  |
| Model  |   |
| product brand name                                 | SIEMENS   |
| product sub brand name                             | VBII  |
| product type designation                           | HEAVY DUTY SWITCH                                       |
| special product feature                            | GROUND LUG INCLUDED                                     |
| type of electrical connection                      | MECHANICAL LUGS   |
| Mechanical Design                                  |   |
| design of the housing                              | TYPE 3R   |
| design of the actuating element                    | SINGLE THROW  |
| material   | STEEL   |
| General product approval                           |   |
| certificate of suitability                         | UL98 / CUL  |

last modified:

12/14/2024 

