SIEMENS

Data sheet for SIMOTICS M-1PH8



Figure similar

Article No. : **1PH8226-1DC05-1FD1**

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Engineering data

		P_N [kW]	M_N [Nm]	I_N [A]	U_N [V]	f_N [Hz]	n_N [rpm]	M_{max} [Nm]	I_{max} [A]	n_{max} [rpm]	M_0 [Nm]	I_0 [A]	η	cos φ	Iμ [A]
Y	**ALM 400V**	**73.0**	**872.0**	**154.0**	**350**	**27.1**	**800**	**2,300**	**380.0**	**4,500**	**872.0**	**154**	**0.940**	**0.830**	**75.0**
	BLM/SLM 400V	68.0	928.0	162.0	310	23.8	700	2,300	380.0	4,500	928.0	162	0.932	0.840	76.0
	ALM 480V	101.0	877.0	154.0	500	37.1	1,100	2,300	380.0	4,500	928.0	154	0.951	0.800	83.0
	BLM/SLM 480V	92.0	879.0	156.0	440	33.8	1,000	2,300	380.0	4,500	879.0	156	0.948	0.820	77.0

Mechanical data

Motor type	Squirrel cage asynchronous motor
Shaft height	225
Cooling	Forced ventilation DE -> NDE
Vibration severity grade	R/A
Shaft and flange accuracy	R
Degree of protection	IP55
Design acc. to Code I	IM V15 with A550 flange
Temperature monitoring	Pt1000 temperature sensor in the stator winding
Color	Standard (Anthracite RAL 7016)
Type of the bearing	Increased cantilever forces
Shaft end	Feather key with full key balancing
Encoder system	Incremental encoder 22 bit with commutation position 11 bit, max. encoder speed = 12000 rpm

Physical constants

Thermal time constant	52 min
Moment of inertia	19,300 kgcm²
Weight (approx.)	740 kg

Connection

Type of electrical connection	Terminal box
Position of the connection	NDE top
Power connection	DE
Signal connection	right
Terminal box designation	1XB7322-P05

Cooling data and sound pressure level

Airflow, min.	0.31 m³/s
Sound pressure level LpA(1m) motor + external fan operation 50 HZ rated load, tolerance + 3dB	73 dB [1]
Air discharge	axial
Pressure drop	650 Pa

External fan

Max. power consumption

1 AC 200 ... 277 V (±10%) 50/60 Hz ±10%	2.0 ... 2.3 A

[1] at a rated frequency of 2 kHz and a speed range of up to 3500 rpm