SIEMENS

Data sheet for SIMOTICS M-1PH8



Figure similar

Article No. : 1PH8184-1JD05-2EC2

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Engineering data

		P_N [kW]	M_N [Nm]	I_N [A]	U_N [V]	f_N [Hz]	n_N [rpm]	M_{max} [Nm]	I_{max} [A]	n_{max} [rpm]	M_0 [Nm]	I_0 [A]	η	cos φ	Iμ [A]
Y	**ALM 400V**	**44.0**	**365.0**	**86.0**	**390**	**39.0**	**1,150**	**925**	**205.0**	**4,600**	**365.0**	**86**	**0.928**	**0.820**	**42.0**
	BLM/SLM 400V	39.0	372.0	87.0	340	34.0	1,000	925	205.0	4,600	372.0	87	0.920	0.830	42.0
	ALM 480V	53.0	337.0	80.0	500	50.6	1,500	925	205.0	4,600	372.0	80	0.940	0.810	42.0
	BLM/SLM 480V	50.0	354.0	84.0	450	45.7	1,350	925	205.0	4,600	354.0	84	0.936	0.820	41.0

Mechanical data

Motor type	Squirrel cage asynchronous motor
Shaft height	180
Cooling	Forced ventilation DE -> NDE
Vibration severity grade	A
Shaft and flange accuracy	N
Degree of protection	IP55
Design acc. to Code I	IM V15 with A450 flange
Temperature monitoring	Pt1000 temperature sensor in the stator winding
Color	Standard (Anthracite RAL 7016)
Type of the bearing	Increased cantilever forces
Shaft end	Feather key with half key balancing
Encoder system	Incremental encoder HTL 2048 S/R, max. encoder speed = 4600 rpm

Physical constants

Thermal time constant	22 min
Moment of inertia	4,890 kgcm²
Weight (approx.)	350 kg

Connection

Type of electrical connection	Terminal box
Position of the connection	NDE top
Power connection	NDE
Signal connection	right
Terminal box designation	1XB7322-P05

Cooling data and sound pressure level

Airflow, min.	0.17 m³/s
Sound pressure level LpA(1m) motor + external fan operation 50 HZ rated load, tolerance + 3dB	73 dB [1]
Air discharge	axial
Pressure drop	550 Pa

External fan

Max. power consumption

1 AC 200 ... 277 V (±10%) 50/60 Hz ±10%	1.1 ... 1.3 A

[1] at a rated frequency of 2 kHz and a speed range of up to 5000 rpm