SIEMENS

Data sheet for SIMOTICS M-1PH8



Figure similar

Article No. : **1PH8186-1ED10-1BC2**

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Engineering data

		P_N [kW]	M_N [Nm]	I_N [A]	U_N [V]	f_N [Hz]	n_N [rpm]	M_{max} [Nm]	I_{max} [A]	n_{max} [rpm]	M_0 [Nm]	I_0 [A]	η	cos φ	Iμ [A]
Y	**ALM 400V**	**58.0**	**482.0**	**112.0**	**390**	**38.9**	**1,150**	**1,230**	**265.0**	**5,000**	**482.0**	**112**	**0.933**	**0.820**	**57.0**
	BLM/SLM 400V	51.0	487.0	112.0	340	34.0	1,000	1,230	265.0	5,000	487.0	112	0.926	0.830	56.0
	ALM 480V	73.0	465.0	110.0	500	50.6	1,500	1,230	265.0	5,000	487.0	110	0.943	0.820	56.0
	BLM/SLM 480V	67.0	474.0	112.0	450	45.6	1,350	1,230	265.0	5,000	474.0	112	0.939	0.820	55.0

Mechanical data

Motor type	Squirrel cage asynchronous motor
Shaft height	180
Cooling	Forced ventilation NDE -> DE
Vibration severity grade	R/A
Shaft and flange accuracy	R
Degree of protection	IP55
Design acc. to Code I	IM B3 (IM B6, IM B7, IM B8, IM V6)
Temperature monitoring	Pt1000 temperature sensor in the stator winding
Color	Standard (Anthracite RAL 7016)
Type of the bearing	Standard
Shaft end	Feather key with full key balancing
Encoder system	Absolut encoder EnDat 2048 S/R, max. encoder speed = 12000 rpm

Physical constants

Thermal time constant	25 min
Moment of inertia	6,520 kgcm²
Weight (approx.)	422 kg

Connection

Type of electrical connection	Terminal box
Position of the connection	NDE top
Power connection	NDE
Signal connection	right
Terminal box designation	1XB7322-P05

Cooling data and sound pressure level

Airflow, min.	0.17 m³/s
Sound pressure level LpA(1m) motor + external fan operation 50 HZ rated load, tolerance + 3dB	73 dB [1]
Air discharge	axial
Pressure drop	550 Pa

External fan

Max. power consumption

1 AC 200 ... 277 V (±10%) 50/60 Hz ±10%	1.1 ... 1.3 A

[1] at a rated frequency of 2 kHz and a speed range of up to 5000 rpm