

Cable Ties

Natural White

Features


- Operating temperature minimum -40° F to maximum 185° F
- UL flame rating 94V-2

Applications

- Safely and easily secures wire bundles and harness components

Standard Material

- 6/6 Nylon



Catalog Number	UPC	Size	Max. Tensile Strength	Per Bag	Ship Case	Weight/ Case	Inches		
							A	Bundle Diameter Min.	Max.
NT0418	21440	4"	18	100	1000	2	.98	.0625	.875
NT0530	21450	5"	30	100	1000	2	.98	.0625	1.378
NT0618	21451	6"	18	100	1000	4	.98	.0625	1.378
NT0640	21452	6"	40	100	1000	4	.142	.0625	1.535
NT0750	21460	7"	50	100	1000	4	.187	.0625	1.75
NT0818	21470	8"	18	100	1000	4	.10	.0625	2
NT0840	21480	8"	40	100	1000	4	.13	.0625	2
NT08120	21490	8"	120	100	1000	5	.30	.0625	2
NT1150	21500	11"	50	100	1000	5	.187	.0625	3
NT1450	21510	14"	50	100	1000	7	.187	.0625	4
NT24175	21530	24"	175	50	500	14	.345	.1875	7.20
NT34175	21550	34"	175	50	500	21	.345	.1875	7.20

Also available in black