

THROUGH ROOF ASSEMBLY, AIR TERMINAL TO IN-LINE CONDUCTOR, ALUMINUM, COPPER, STAINLESS STEEL 18-8 (EN 1.4305), 5/8 UNC THREAD

CATALOG NUMBER

LPC626A58



CERTIFICATIONS



FEATURES

Allows for lightning protection conductors to be concealed in ceiling or walls

PRODUCT ATTRIBUTES

Conductor Size, UL: Class 1 - Class 2 (4/0 Max)

Material: Aluminum;Copper;Stainless Steel 18-8 (EN 1.4305)

Connection Material, Air Terminal: Aluminum

Connection Material, In-Line Conductor: Copper

Thread Size: 5/8" UNC

Rod Length: 12"

Rod Size: 1/2"

Unit Weight: 1.070 lb

ADDITIONAL PRODUCT DETAILS

Always consult the roof manufacturer or owner for proper flashing materials.

DIAGRAMS



WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

North America

+1.800.753.9221
Option 1 – Customer Care
Option 2 – Technical Support

Europe

Netherlands:
+31 800-0200135
France:
+33 800 901 793

Europe

Germany:
800 1890272
Other Countries:
+31 13 5835404

APAC

Shanghai:
+ 86 21 2412 1618/19
Sydney:
+61 2 9751 8500



Our powerful portfolio of brands:
nVent.com CADDY ERICO HOFFMAN RAYCHEM SCHROFF TRACER