



THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.

OPEN VIEW



ADHESIVE BACKING  
PRESSURE SENSITIVE  
FOAM .040 (1.0) THICK  
WITH PROTECTIVE LINER.

CLOSED VIEW



- NOTES:
- VISIT OUR ON-LINE CATALOG AT WWW.PANDUIT.COM FOR A LIST OF ADDITIONAL PART NUMBER SUFFIXES TO INDICATE COLOR AND/OR PACKAGE QUANTITY.
  - PART IS DESIGNED TO SUPPORT MAXIMUM WEIGHT ON A CLEAN, DRY, SMOOTH SURFACE. THE SURFACE MUST BE PROPERLY PREPARED IN ACCORDANCE WITH PANDUIT RECOMMENDATIONS.
  - PANDUIT RECOMMENDATIONS:
    - IT IS RECOMMENDED THAT PANDUIT ADHESIVE TAPE BE APPLIED ON SURFACES WHOSE TEMPERATURE IS APPROXIMATELY 70°F (21°C) OR HIGHER FOR THE INITIAL BOND.
    - THE OPTIMUM RECOMMENDED DWELL TIME PRIOR TO LOADING FOR RUBBER ADHESIVE IS TWO HOURS.
    - PANDUIT TAPE SHOULD BE APPLIED TO A CLEAN, DRY, GREASE-FREE SURFACE WITH SUFFICIENT PRESSURE TO ASSURE GOOD ADHESIVE CONTACT. AVOID ADHESIVE CONTAMINATION WITH FOREIGN MATERIAL BY CLEANING WITH AN ISOPROPYL ALCOHOL OR A DREGREASER.
  - TO APPLY PART:
    - REMOVE PROTECTIVE LINER.
    - PLACE PART IN DESIRED LOCATION.
    - APPLY PRESSURE TO FLAT SURFACE OF PART.
  - NO WARRANTY, EXPRESSED OR IMPLIED, IS MADE BY PANDUIT WITH RESPECT TO ADHESIVE BOND PERFORMANCE. THE CONDITIONS UNDER WHICH THESE MOUNTS MAY BE APPLIED AND/OR THE SURFACE TO WHICH THEY ARE APPLIED ARE BEYOND PANDUIT'S CONTROL.
  - DIMENSIONS IN METRIC ARE IN [ ].

PART NAME	PANDUIT PART NUMBER (SEE NOTE 1)	COLOR	LENGTH in. (mm.)	STATIC LOAD (SEE NOTE 2)	APPROX. WEIGHT
LATCHING DUCT	LD3**6-A	-----	72.0±.13 (1829±3.3)	.30 lbs/in (5.4 g/mm)	.045 lbs/ft (.067 g/mm)
LATCHING DUCT	LD3**8-A	-----	96.0±.13 (2438±3.3)	.30 lbs/in (5.4 g/mm)	.045 lbs/ft (.067 g/mm)
LATCHING DUCT	LD3**10-A	-----	120.0±.13 (3048±3.3)	.30 lbs/in (5.4 g/mm)	.045 lbs/ft (.067 g/mm)

PART NUMBER

LD3

TITLE

LATCHING DUCT

CUSTOMER DRAWING

ITEM REVISION NAME	D201038A/05
DATASET FILE NAME	D201038A_DC_LD3/05A
<p>THIRD ANGLE PROJECTION</p>	
MATERIAL	PVC
DRAWN BY	GDN
DATE	07-30-85
CHK	WJB
SCALE	NONE
DRAWING NUMBER	SS-20103
SHEET 1 OF 1	A



SS-20103

RELEASED TO PRODUCTION

DESCRIPTION

TAM

BSN

BY

DATE

REV

ECN

DESCRIPTION

APR

CHK

BY

DATE

REV

ECN

DESCRIPTION

APR

CHK

BY

DATE

REV

ECN

DESCRIPTION

APR

CHK

BY

DATE

REV

ECN

DESCRIPTION

APR

CHK

BY

DATE

REV

ECN

DESCRIPTION

APR

CHK

BY

DATE

REV

ECN

DESCRIPTION

APR

CHK

BY

DATE

REV

ECN

DESCRIPTION

APR

CHK

BY

DATE

REV

ECN

DESCRIPTION

APR

CHK

BY

DATE

REV

ECN

DESCRIPTION

APR

CHK

BY

DATE

REV

ECN

DESCRIPTION

APR

CHK

BY

DATE

REV

ECN

DESCRIPTION

APR

CHK

BY

DATE

REV

ECN

DESCRIPTION

APR

CHK

BY

DATE

REV

ECN

DESCRIPTION

APR

CHK

BY

DATE

REV

ECN

DESCRIPTION

APR

CHK

BY

DATE

REV

ECN

DESCRIPTION

APR

CHK

BY

DATE

REV

ECN

DESCRIPTION

APR

CHK

BY

DATE

REV

ECN

DESCRIPTION

APR

CHK

BY

DATE

REV

ECN

DESCRIPTION

APR

CHK

BY

DATE

REV

ECN

DESCRIPTION

APR

CHK

BY

DATE

REV

ECN

DESCRIPTION

APR

CHK

BY

DATE

REV

ECN

DESCRIPTION

APR

CHK

BY

DATE

REV

ECN

DESCRIPTION

APR

CHK

BY

DATE

REV

ECN

DESCRIPTION

APR

CHK

BY

DATE

REV

ECN

DESCRIPTION

APR

CHK

BY

DATE

REV

ECN

DESCRIPTION

APR

CHK

BY

DATE

REV

ECN

DESCRIPTION

APR

CHK

BY

DATE

REV

ECN

DESCRIPTION

APR

CHK

BY

DATE

REV

ECN

DESCRIPTION

APR

CHK

BY

DATE

REV

ECN

DESCRIPTION

APR

CHK

BY

DATE

REV

ECN

DESCRIPTION

APR

CHK

BY

DATE

REV

ECN

DESCRIPTION

APR

CHK

BY

DATE

REV

ECN

DESCRIPTION

APR

CHK

BY

DATE

REV

ECN

DESCRIPTION

APR

CHK

BY

DATE

REV

ECN

DESCRIPTION

APR

CHK

BY

DATE

REV

ECN

DESCRIPTION

APR

CHK

BY

DATE

REV

ECN

DESCRIPTION

APR

CHK

BY

DATE

REV

ECN

DESCRIPTION

APR

CHK

BY

DATE

REV

ECN

DESCRIPTION

APR

CHK

BY

DATE

REV

ECN

DESCRIPTION