

SKU: LSN-100NE

UPC: 0783669006315

Features & Benefits:

Description: Permaground Copper Eye-Bolt Terminal, Conductor Range 1000-2/0 Sol, 1/4-3/4in Mounting Surface

Specs

Additional Class Attributes

Connection	Mechanical
Number of Conductors	1
Wire Orientation	Parallel

Dimensions

Drive Size Main	3/4
Drive Type Main	External Hex
Height (IN)	4.5
Height BX (IN)	6.5
Length (IN)	1.719
Weight (LB)	1.5
Weight BX (LB)	46.5
Width (IN)	1.688
Width BX (IN)	12.75

Material and Finish

Conductor Material	Copper
Connector Finish	NA
Insulation	NA
Material	Copper/Aluminum Bronze Alloy

Additional Technical Specifications

Conductor Type	Solid

Bolt and Screw Sizes

Clamping Bolt Size	1/2
Number of Wire Binding Screws per Port	0
Wire Binding Screw Size	NA

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 30
Direct Burial	No
Dual Rated	No
NEMA Code	0-000-1
UPC Code	78366900631

Testing Standards

Prop65 Compliance	This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation
UL Control Number	NA
UL File Number	NA

Color

Color	Copper

Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)	NA
Conductor Range AL Stranded (Primary, run, main, line)	NA
Conductor Range AL Stranded (Secondary, tap, load)	NA
Conductor Range CU Solid (Primary, run, main, line)	4/0 Sol - 2/0 Sol
Conductor Range CU Solid (Secondary, tap, load)	NA
Conductor Range CU Stranded (Primary, run, main, line)	1000 kcmil - 2/0 Str
Conductor Range CU Stranded (Secondary, tap, load)	NA
Conductor Range AL Solid (Primary, run, main, line)	NA